

DHABA @ DIAL			
MUFFIN DESIGN SOLUTIONS			
PLUMBING WORKS-WATER SUPPLY AND DRAINAGE WORKS			
Sl. No	DESCRIPTION	UNIT	QTY
I INTERNAL WATER SYSTEM			
(A)	WATER DISTRIBUTION FOR ALL THE AREAS		
(A)	SUB-TOTAL FOR WATER DISTRIBUTION FOR ALL THE AREAS		
(B) INTERNAL SEWERAGE WATER SYSTEM + BOH/BAR AREA			
1	Supplying, fixing, testing and commissioning PVC, waste pipes (SWR) confirming to IS13592 :1992, type B with rubber ring (confirming IS:5382) joint inclusive of all necessary specials like bends, tees, offsets, door ends, junctions, cowls, etc., laid under floor/fixed on walls and in pipe shafts etc., complete. The quoted rate should include necessary earthwork, chasing in walls, making bores in walls, foundations and slabs and making good the chased surfaces, Anchor fasteners, supports like hanger supports, MS brackets with GI clamps, grip bolts, etc., complete. (Note:GI brackets/Supports shall be provided at every 1.5m c/c)		
INTERNAL DIA			
1	75 mm dia	Rmt	15 <i>9 mtr</i>
2	Supplying, fixing and testing PVC pressure pipes (6Kg/sqcm) confirming to IS 4985 for waste connection from wash basin to 'P' trap and sink outlet pipe with solvent joints, including all the fittings, laid above false ceiling concealed in wall etc, complete. The quoted rate should include necessary chasing in walls making good the same in C.M 1:4, necessary fittings viz., supports like Hi-tech supports, grip bolts elbows, tees etc., with G.I clamps and Brackets, Anchor fasteners, Grip bolts, nuts and bolts, etc, complete.		
3	40mm dia Flexible pipe for the drawing from the sink to the grease trap + from the sink to the outlet pipe	Rmt	5 ✓
6	Supply & Fixing of Floor drain with anticroached trap Chilly make model number CCT-SG-129 Square Gypsy 129*129 mm & 31mm hole for waste pipe with necessary fittings etc., complete.	Each	4 ✓
7	Supply & Fixing of Water heater of 15lts of Jaquar Make Model No. ELM-WHT-V025 Angular stop cock with wall flange of Jaquar Make Model No CON-CHR-059KN, 2nos 450mm long SS bridged hose with M10x1nipple, 15mm nut, O-ring & rubber wahser with necessary fittings etc., complete. Water heater to be rated for 7 Kg/cm2 Inlet pressure.	Each	1 ✓

OK
Stamped
02/8/24

Signature
7/8/2024
Saran nishy