# M/S JAGANNATH ENTERPRISE

GSTIN 19ATGPJ3421R1Z8 PAN ATGPJ3421R

32/1 14

NEW CORD ROAD,, MULAJORE NUTUN PARA, ATHPUR, North Twenty Four Parganas, WEST BENGAL, 743128

Mobile +91 8697739690 Email info.jagannathenterprise@gmail.com

Invoice #: JE/24-25/-95

Invoice Date: 18 Nov 2024

**Due Date: 18 Nov 2024** 

**Customer Details:** 

**Billing Address:** 

**Shipping Address:** 

**GSTIN: 19AADCB2762L1ZF** 

TRAVEL FOOD SERVICES PRIVATE LIMITED N.S.C.B. INTERNATIONAL AIRPORT VIP Road, Kazi Nazrul Islam Sarani, Dum Dum,

Kolkata,

Kolkata, WEST BENGAL, 700052

Kolkata Maintenance N.S.C.B. INTERNATIONAL AIRPORT VIP Road, Kazi Nazrul Islam Sarani, Dum Dum,

Kolkata,

Kolkata, WEST BENGAL, 700052

Place of Supply: 19-WEST BENGAL

PO Number: TFSKPL/PO/24-25/000086

#	Item	Rate / Item	Qty	Taxable Value	Tax Amount	Amount
1	Demolition & Dismantling the existing dado tile SAC: 9984 Kolkata Street	35.00	220 SQF	7,700.00	1,386.00 (18%)	9,086.00
2	Providing and fixing in position Glazed Vitrified Dado Tile SAC: 9984 Kolkata Street	170.00	220 SQF	37,400.00	6,732.00 (18%)	44,132.00
3	Removing and Cartying away the Debris post completion of work from site to the dumping location, all complete as per instruction from the Site engineer Incharge SAC: 9984 Kolkata Street	45.00	160 LOT	7,200.00	1,296.00 (18%)	8,496.00
4	Providing & applying Emulsion Paint SAC: 9984 Subway	38.00	700 SQF	26,600.00	4,788.00 (18%)	31,388.00
5	Demolition & Dismantling of Existing Flooring SAC: 9984 DOM LOUNGE FLOOR	35.00	250 SQF	8,750.00	1,575.00 (18%)	10,325.00
6	Providing and fixing in position Glazed Vitrified Tile flooring SAC: 9984	170.00	180 SQF	30,600.00	5,508.00 (18%)	36,108.00

ltem	Rate / Item	Qty	Taxable Value	Tax Amount	Amount
Proving & Laying machine cut, machine polished approved 25mm thick Kota stone flooring, stone to be machine cut, machine polished, laid in pattern and sizes as detailed in drawing or as directed by PM, bedded over cement, sand mortar of mix ratio of 1:6 (1 cement: 6 sand) including cleaning and preparing the surface for bedding, spreading neat cement slurry by using minimum cement about 2 kg/sqm prior to bedding and spreading cement paste using minimum cement about 4.5 kg/sqm over bedding, joints to be cleaned and grouted with matching colour approved quality polymer based readymade grout, curing, machine polishing, cleaning, etc. to required line, level, etc. all complete at all depths, heights and leads to the satisfaction of the PM. Basic rate of Kota @60/- Sqft SAC: 9984	170.00	60 SQF	10,200.00	1,836.00 (18%)	12,036.00
			CGST	9.0%	₹1,28,450.00 ₹11,560.50 ₹11,560.50
	Proving & Laying machine cut, machine polished approved 25mm thick Kota stone flooring, stone to be machine cut, machine polished, laid in pattern and sizes as detailed in drawing or as directed by PM, bedded over cement, sand mortar of mix ratio of 1:6 (1 cement: 6 sand) including cleaning and preparing the surface for bedding, spreading neat cement slurry by using minimum cement about 2 kg/ sqm prior to bedding and spreading cement paste using minimum cement about 4.5 kg/sqm over bedding, joints to be cleaned and grouted with matching colour approved quality polymer based readymade grout, curing, machine polishing, cleaning, etc. to required line, level, etc. all complete at all depths, heights and leads to the satisfaction of the PM. Basic rate of Kota @60/- Sqft	Proving & Laying machine cut, machine polished approved 25mm thick Kota stone flooring, stone to be machine cut, machine polished, laid in pattern and sizes as detailed in drawing or as directed by PM, bedded over cement, sand mortar of mix ratio of 1:6 (1 cement: 6 sand) including cleaning and preparing the surface for bedding, spreading neat cement slurry by using minimum cement about 2 kg/ sqm prior to bedding and spreading cement paste using minimum cement about 4.5 kg/sqm over bedding, joints to be cleaned and grouted with matching colour approved quality polymer based readymade grout, curing, machine polishing, cleaning, etc. to required line, level, etc. all complete at all depths, heights and leads to the satisfaction of the PM. Basic rate of Kota @60/- Sqft	Proving & Laying machine cut, machine polished approved 25mm thick Kota stone flooring, stone to be machine cut, machine polished, laid in pattern and sizes as detailed in drawing or as directed by PM, bedded over cement, sand mortar of mix ratio of 1:6 (1 cement: 6 sand) including cleaning and preparing the surface for bedding, spreading neat cement slurry by using minimum cement about 2 kg/ sqm prior to bedding and spreading cement paste using minimum cement about 4.5 kg/sqm over bedding, joints to be cleaned and grouted with matching colour approved quality polymer based readymade grout, curing, machine polishing, cleaning, etc. to required line, level, etc. all complete at all depths, heights and leads to the satisfaction of the PM. Basic rate of Kota @60/- Sqft	Proving & Laying machine cut, machine polished approved 25mm thick Kota stone flooring, stone to be machine cut, machine polished, laid in pattern and sizes as detailed in drawing or as directed by PM, bedded over cement, sand mortar of mix ratio of 1:6 (1 cement : 6 sand) including cleaning and preparing the surface for bedding, spreading neat cement slurry by using minimum cement about 2 kg/ sqm prior to bedding and spreading cement paste using minimum cement about 4.5 kg/sqm over bedding, joints to be cleaned and grouted with matching colour approved quality polymer based readymade grout, curing, machine polishing, cleaning, etc. to required line, level, etc. all complete at all depths, heights and leads to the satisfaction of the PM. Basic rate of Kota @60/- Sqft SAC: 9984  Taxable Am CGST	Proving & Laying machine cut, machine polished approved 25mm thick Kota stone flooring, stone to be machine cut, machine polished, laid in pattern and sizes as detailed in drawing or as directed by PM, bedded over cement, sand mortar of mix ratio of 1:6 (1 cement : 6 sand) including cleaning and preparing the surface for bedding, spreading neat cement slurry by using minimum cement about 2 kg/ sqm prior to bedding and spreading cement paste using minimum cement about 4.5 kg/sqm over bedding, joints to be cleaned and grouted with matching colour approved quality polymer based readymade grout, curing, machine polishing, cleaning, etc. to required line, level, etc. all complete at all depths, heights and leads to the satisfaction of the PM. Basic rate of Kota @60/- Sqft

Total

₹1,51,571.00

Total Items / Qty : 7 / 1,790

Total amount (in words): INR One Lakh, Fifty-One Thousand, Five Hundred And Seventy-One Rupees Only.

**Amount Payable:** 

₹1,51,571.00

#### **Bank Details:**

Bank:

**CANARA BANK** 

Account #:

97073070002972

IFSC Code:

CNRB0019707

Branch:

**SHYAMNAGAR** 



For M/S JAGANNATH ENTERPRISE

**Authorized Signatory** 

#### Notes:

None

#### **Terms and Conditions:**

- 1) JOB DONE WITHIN 2 TO 3 WEEKS FROM THE DATE OF ORDER & ADVANCE .
- 2) FREIGHT EXTRA AT ACTUAL PAID BY CUSTOMER .
- 3) PAYMENT: 70% ADVANCE ALONG THE ORDER & BALANCE 30% AFTER INVOICE SUBMITED.
- 4)INTEREST @ 24% PER ANNUM WILL BE CHARGED IF PAYMENT NOT MAKE WITHIN 30 DAYS FROM BILL DATE.
- 5) PAYMENT SHOULD BE MADE BY A/C PAYEE CHEQUE/ONLINE TRANSFER
- 6) ALL SUBJECT TO BARRACKPORE JURISDICTION.

Receiver's Signature

## **Purchase Order**

### TRAVEL FOOD SERVICES KOLKATA PRIVATE LIMITED

Order Number: TFSKPL/PO/24-25/000086

Supplier Detail	Shipped Location	Invoice Location
Jagannath Enterprise Supplier Code : RV232415547 [ V0000794 ]	TRAVEL FOOD SERVICES KOLKATA PRIVATE LIMITED Kolkata Airport	TRAVEL FOOD SERVICES KOLKATA PRIVATE LIMITED Kolkata Airport
(V0000794)	N.S.C.B. INTERNATIONAL AIRPORT VIP Road, Kazi Nazrul Islam Sarani, Dum Dum, Kolkata, West Bengal, 700052	83, Gale No. 3C, N.S.C.B. International Airport Vip Road, Kazi Nazrul Islam Sarani, Dum Dum, Kolkata, West Bengal, 700052 GSTIN No : 19AAECT8193L1ZJ
PAN No : ATGPJ3421R Supplier GST No : 19ATGPJ3421R1Z8 Supplier Contact No : Contact Person Name : JHUMA BASAK Supplier Email : info.jagannathenterprise@gmail.com	Cost Center Code: 90360001 Cost Center Name: Projects and Maintenance Project ID: PO Category: Maintenance	Payment Term: Payment to be done as per actual verification of quantities and billing PO Creation Date: 19/07/2024 PO Approval Date: 30/07/2024 PO Currency: INR Buyer Name: Binu Balachandran

Sr. No	Item Code	HSN/SAC	Item Name	Item Description	Pur. Grp.	Qty	UOM	Basic Rate	Dis%	Net Rate	Total Amount	SGST %	CGST %	Gross Total Amount
1		9984	Demolition & Dismantling of Existing Flooring	Demolition & Dismantling the existing flooring, upto required base morfar, pcc concrete as per required. Cost to include carting away all debris from site, lead and lifts, material, labours, transportation and all other incidental charges etc. complete and as directed by Site Engineer	B01	3,000.00	SFT	35.00	0.00	35.00	105,000.00	9	9	123,900.00
2		9984	Removing and Cartying away the Debris	Removing and Cartying away the Debris post completion of work from site to the dumping locallon, all complete as per instruction from the Site engineer Incharge	B01	5,500.00	LOT	45.00	0.00	45.00	247,500.00	9	9	292,050.00
3		9984	Providing & Laying Plain cement concrete	Providing & Laying Plain cament concrete of size 50 75 100mm thk. of specified grade (M10) including the cost of centering and shuttering & required curing. Approved make cament is PPC (ACC, Ultra tech, Birla)	B01	3,000.00	SFT	140.00	0.00	140.00	420,000.00	9	9	495,600.00

4	9984	Providing and	Providing and	B01	1,500.00	AFF	170.00	0.00	170.00	222 222 22		0	000 000 00
	9904			BOI	1,500.00	SFT	170.00	0.00	170.00	255,000.00	9	9	300,900.00
2		fixing in position Glazed Vitrified	fixing in position		0								
0.0			Glazed Vitrified	0 1	l Y					l l	1		
11 11	1	Tile flooring	Tile flooring as	6	i )								
l II	- 1	4	per detail in									1	4
1 1			drawing, It shall	1	Y Y								
1 1			be fixed with										
1 1			cement mortar of		l i								
1 1			1:4, (required										
1 1		1	mortar bed is	1		ł	1	ł	l l				
			25mm to 50mm										
1 1			thk) with thick		1	l .							
1 1			grey cement		1								
			slurry, using								1		
1 1			cement grout.	1							1	l I	
1 1			The job including	1					1		1	l F	
1 1			cutting of tiles &	1							1		
1 1			making smooth	1	(			1					
1 1			edges wherever								i - 8		
1 1			required for drain					1					
1 1			pipes. The work								1 8		
1 1			shall also include										
1 1		13	cost of materials,									1	1
1 1			wastages, labour,			1		Ÿ			1		
1 1	1	1	all lead and lift at									1 1	1
1 1	1	1	all levels, loading	1									
1 1	1	1	and unloading,	1								1	
1 1			transportation,	1		1							
1 1			curing etc. and all	1								l	
1 1			other incidental	1 3		1						1	
1 1			charges etc.,									l l	
1 1			complete and as		1					1			l I
1 1	1		directed by				1						
4 E	100		Engineer-in-char	1			1	1					
1 1	7 1		ge. The cost		1			1					
1 1			should include		1			1				0	
1 1				1	I			1					1
			PVC floor	1	I			1					[ ]
1 1			covering material.		1				6				
1 1		Ĭ.	Including								1		[
1 1			Corrugated sheet	1			l l	1				II,	1
1 1	ľ		Plastic sheet for		1								
1 1			tile Protection .		1			II.					
1			(size - 600x600		1		0			1			
			mm)		1					1			

6.1	9984	Image days 6	True de la contraction	B01	1,500.00	OFT	170.00	0.00	170.00	000,000,00	9	9	300,900.00
5	9984	Proving &	Proving & Laying	BUT	1,500.00	SFT	170.00	0.00	170.00	255,000.00	8	8	300,800.00
		Laying machine	machine cut,								- 1		
		cut, machine	machine polished	1							- 1	1	
	- 1	polished	approved 25mm								- 1	- 1	
1 4	1	approved Kota	thick Kota stone	1			1 1	( )		0	- 1		
1. 1	1	stone flooring	flooring, stone to	1 0	1		1						
1 1		Storio nocimig	be machine cut,		1 1								
				1 1	1								
11 1	1		machine									1 (	
	1	1	polished, laid in	1				1 3					
	1		pattern and sizes	1									
1 1	- 1		as detailed in	1							1	1	
1 1			drawing or as	1	1				1		1		
			directed by PM,										
1 1	1	(	bedded over	1	(i )				1		1	1 11	
1 1													
1 1			cement, sand							1		1 - 1	
1 1			mortar of mix							(1)		1 9	
ш.	il.	1	ratio of 1:6 (1	1	0 (								
U H			cement : 6 sand)	1			1					1 //	
		1	Including	L .									
1		1	cleaning and		1 1								
1 1		П	preparing the		1 .	l							
1 1				1	1								2
1 1			surface for	1	1 :	l						1	1
l li			bedding,	1							1		
1 1		1	spreading neat	ł	l .			1					
1			cement slurry by	1		(1)		1					
	3		using minimum	1							4 3		
0 III			cement about 2	1	1		1						
r a	, a	- 10	kg per sqm prior		1	1		1			0 /		
1 1			to bedding and								1 /		
1 1			spreading		1								
1 1											1	- 1	
1 1		1	cement paste	1								1 1	
1 1		110	using minimum	1						l).	l ï		
1 1	1		cement about 4.5	1			1	1	1	Ü.		1	
1 1			kg per sqm over	1				1				1	l
1 1			bedding, joints to	1	1								
1 1		10	be cleaned and	1				N 1					
1 1			grouted with	1	1	T.			II .				
1 1			matching colour	1	1				N. Control of the Con			l	
1 1				1	1			1					
1 1	ľ	1	approved quality	1		li .	1		Tr.		1	1	
1 1			polymer based	1			1	1					
1 1	(1)		readymade grout,	4				1				1	
1 1			curing, machine	1	1			1				1	
1 1			polishing,	1	1	1		1	I .		1		
i i			cleaning, etc. to	1	100				E		1		t .
1 1			required line,	1	1				l)				
1 1	Y	1	level, etc. all	1	1			1				F	
1 1					1		1	1			1		Į.
1 1			complete at all	1	1	1		10			1		I.
1 1		ľ	depths, heights	1		1	1	1		1	l	1	
		1		11					1				

			and leads to the										1
•			satisfaction of the PM. Basic rate of Kota @60 Rs Sqft										
6	9984	Demolition & Dismanding the existing dado tile	Demolition & Dismantling the existing dado tile including cement mortar as per required. Cost to include carting away all debris from site, lead and ilfts, material, labours, transportation and all other incidental charges etc. complete and as directed by Site Engineer.	B01	1,500.00	SFT	35.00	0.00	35.00	52,500.00	9	9	61,950.00
7	9984	Providing & Laying Plain cement plaster	Providing & Laying Plain cement concrete of 15 mm thick cement plaster with base preparation for fixing of new dado tiles. Approved make cement is PPC (ACC, Ultra tech , Birla)	B01	1,500.00	SFT	60.00	0.00	60.00	90,000.00	9	9	106,200.00

8	9984	Providing and	Providing and	B01	1,500.00	SFT	170.00	0.00	170.00	255,000.00	9	9	300,900.00
1	1	fixing in position	fixing in position							9	- 1		
1	- 1	Glazed Vitrified	Glazed Vitrified								- 1		
	- 1	Dado Tile	Dado Tile as per	1							- 1		
	- 1		detail In drawing.								- 1		
1	- 1		It shall be fixed	1	1				1		- 1		
	- 1		with cement	1	1 1						- 1		
	- 1		mortar with thick								- 1		
4	- 1	1	grey cement		1 1					TI I	1		
	- 1		slurry, using		1								
1			cement grout.	1				1					
	- 4		The job including	1								1	
	1	1	cutting of tiles &	1					(1)				
	1		making smooth		1			1					
			edges wherever		1								
			required for		11 3					1			
		1	services. The							1		1 9	
	1		work shall also	l									
			include cost of							J			
	1	4	materials,	b	1 /			1 8				9	
			wastages, labour,										
	1		all lead and lift at						l A				
	1		all levels, loading					1			1 1		
- 1	1	1	and unloading,		1 3			1 1					
	TI .		transportation,									1 0	i.
	1	10	curing etc. and all	1		1		1			1 0		
	1	110	other incidental	1	1			1			1		
	1		charges etc.,	1				1	1				
			complete and as		1							1	
1			directed by		1				1				
			Engineer-in-char										
	1		ge. The cost										
1		1	should include	1	1				1			1 8	ľ
			PVC floor									)	
	30		covering material.	1									l
			Including	1	1 0		V.						
		1	Corrugated sheet	1	1			1	1				
			Plastic sheet for										l .
	414		tile Protection .	1	4			1					li .
	- 1	5	(size - 300x600	1	1			1					
	1		mm)					1				1	

[0]	Inna.	In-malwa 6	TD	Ino.	4 000 00		65.00	0.00	05.00				11.000.001
9	9984	Demolition &		B01	1,000.00	SFT	35.00	0.00	35.00	35,000.00	9	9	41,300.00
3	l l	Dismantling the	Dismantling the									- 1	
11	l l	existing wall,	existing wall, Wall						l.		- 1	- 1	
1 1		Wall Plaster,	Plaster, POP,								- 1		1
		POP, Putty,	Putty, Panelling,	1								1	1
		Panelling, etc.	etc. upto required										1
1 (			and as per	1							1		
			instruction from	1	1								
			the site Engineer								1		1
J.			Incharge. Cost to	] .	J.							- 0	1
			include carting	1	1		ľ					1	1
			away all debris	1 /									
10 0			from site, lead	1 (									
		1	and lifts, material,	1					1		1		
1 0		1	labours,	1									
0.0		1	transportation	1	8								i
		1	and all other	1				1	1.				
			incidental								1		
			charges etc.		ľ.						1		1
			complete and as				1		1				
		1	directed by Site										
		1											
			Engineer										

10	9984	Providing and	Providing and	B01	1,000.00	SFT	92.00	0.00	92.00	92,000.00	9	9	108,560.00
100	0007	applying Wall	applying 12mm		114400000000000000000000000000000000000	0.7	Carata and	( New York Cont.)	05900	2014/12/12/20	1650	3.72	NASTATE BUTCHES
1 0		Plaster	thick plaster with	1 3						1	- 1	1	
1 1		Lippici	premix mortar	1			8				- 1		
1 1			mix of ratio CM	1 1							- 1	1	
1 1		1		1 1	/					1	- 1		
1 1		1	1:4 (1 cement : 4	1 1	W 1					1	- 1		
1 1			sand) with alr	1 /					1		- 1		9
	1		entraining agent								- 1		
1 1	- 1		Cebex 112,	1							- 1		
	- 1		150ml per bag of	1						7			
1 1			cement, to	10 1			1				1	1	
1 1			internal surfaces		1								
1 1			of concrete and						1 1	1			
1 1	1	1	masonry work;	1				1 1	1	11	1		
1 1	1		including raking					1 1	1		1 1		
1 1	1		out joints,										
	1		hacking concrete	1									
	1	1	surfaces and	1	1		}		l I				
1 1	1	1	applying						l A				
1 1			approved	ľ	1								
1 1	- 1		chemical bonding					1				1	
1 1	1	1											
E 31	1	1	agent for	1	1					1			
1 1	1	YI .	receiving cement	1					1				
1 1			finished dash	1		1		1		1			U I
1 11	N.		coat plaster and			1						(0	0
1 1	0	N.	applying a		1	1		1 3	1			10	9) ()
1 1			scratch coat over						1			1	0 0
1 1			concrete		1	1							1
1 1	- 1	4.	surfaces by	1		l		l					
1 1	- 1		bonding adhesive	1	1	l		1					
1 1	1		chemical coat as	1	1								
1 1			directed by	1	1								
1 1			approved										
1 1			manufacturer to	1	1								1
1 1			create a key,	1									
1 1	110	1	cleaning grooving	1								1	
1 1			deep junctions of	1	1			1				1	
1 1			concrete &	1		1		1				1	
1 1					1			1					
1 1			masonry,	1	1								
			grouting then	1	1		4	1					K
1 1	1		back by mortar	1	1		1	1				1	
	710		mixed with non	1	1			1				1	
1 1			shrinking	1	1			1				1	1
	L	1	compound along	1	1			10			1		1
	U		with packing of	4			k)	l .					1
			clean, fresh	1	4		8					I.	1
			square cut	4							1	1	
			aggregate; also	1							1		
1 1			DOMESTIC STATE OF THE PARTY OF	1									

-	G.		iding and						
l.	1900	fixing	20 gauge			1			1
	1	PVC	mesh @	1 1		1			1
	1	150 r	mm wide to	1 1		1		1	1
1	1	juncti	tions of			T I			1
1		conc	rete and	1 1	1				1 1
1		maso	onry,	1 1	- 1			1	
1			aring jambs,		1			- 1	
1			grooves,		1	1		- 1	1
	8		is, wattas,		J				1
1			ding of		1	1		1	
1			ers, all	1 1	1	1		1	1
			plete as per			1			1
		archi	itectural			- 3			1 1
b.			/ings,	1 1		8			1 8
1	1		rifications	1 1		1			l i
1	(1)		finished	1 1	il .	)]			1 1
1			oth with				() ()		
1	1		den rundha		- 4	1		1 1	
1			s specified by			1		1	
1			PM at all			1	ll l	- 1	1
			s, depth and			A l			
		lifts.	doing						
1	1		pendent			1		1	1
1			ole-legged			4		- 1	
			folding,						1
1			ning of	1 1	8				
1			aces, curing,			4		1	1
1			plete as per			1			
1	T .	spec	cification and	1 1			1		
1		to the	e approval of			1	P 0		
1			PM. (Location				1	1	
1			rtical wall						
			ition wall of						1
1			type)						1 1
_		I I I I I I I I I I I I I I I I I I I	71-7						

11	9984	Removing of Existing Wall Paint	Removing of Existing Wall Paint: Scrubbing, Removing of existing wall paint by using appropriate grade sand paper upto the required finish. The surface shall be ready as per the approved instruction from the Site incharge all complete.	B01	8,000.00	SFT	15.00	0.00	15.00	120,000.00	9	9	141,600.00
12	9984	Providing & applying Emulsion Paint	New Paint: Providing & applying Three (03) coats of approved Plastic paint on the exposed surface of wall, ceiling, Partition, etc. The cost also includes applying of 2 layers of approved quality and make wall car putty, rubbing the same surface with appropriate sand paper, finishing and maintening the surface upto required, all complete with final coat no brush mark to be visible after painting colour shade as specified.	B01	8,000.00	SFT	36.00	0.00	38.00	304,000.00	9	9	358,720.00

13	9984	Furniture - Additional Cushioning	Additional Cushioning_ Providing, applying and fixing additional Cusioning at the base upto the required finishing as per the approved quality.	D01	270.00	SFT	180.00	0.00	180.00	48,600.00	9	9	57,348.00
14	9984	Furniture - Base Fixing	C. Base Fixing_ Repairing, refixing, installation and maintening the existing furniture base work that involves Wood work, Joinery, polishing, etc. all includes necessary hardware and fixtures, all complete as per site incharge	D01	270.00	NOS	2,250.00	0.00	2,250.00	607,500.00	9	9	716,850.00
15	9984	Furniture - Upholstery_ Repairing - Leatherite	D. Upholstery_ Repairing and maintening re-upholstery as per the approved leatherite.	D01	1,000.00	MTR	625.00	0.00	625.00	625,000.00	9	9	737,500.00
16	9984	Furniture - Upholstery_ Repairing - Fabric	D. Upholstery_ Repairing and maintening re-upholstery as per the approved fabric.	D01	350.00	MTR	350.00	0.00	350.00	122,500.00	9	9	144,550.00

Total Qty: 38,890.00

 Total Basic PO Amount
 3,634,600.00

 Total Other Charges
 327,114.00

 CGST Amount
 327,114.00

4,288,828.00

Grand Total PO Amount

Amount In Words: Rupees Fourty Two Lakh Eighty Eight Thousand Eight Hundred Twenty Eight Only

Remarks: This PO is for annual rate contract based upon the quantity volumes shared by maintainance team

Standard Terms And Condition :

Completion / Delivery TimeLine :

Mobilization Date : Defects Liability Period : Retention Percentage : 0

Escalation Buyer Detail						
Name	Mobile No.	Email - ID				
Mrunal Joshi	8390813805	mrunal.joshi@k-corp.in				
Binu Bakachandran	0000000000	binu.balachandran@k-corp.ln				

#### Disclaimer :

Point 1: Unless informed to us it is assumed that you are not registered as MSME with the respective government authority. If you have not yet provided the MSME details along with proof kindly provide the same at the earliest. Alternatively once you get registered then provide us relevant proof to update our records.

Point 2: Supplier is requested to acknowledge or decline the order within 24 hours or else it would be considered as accepted.

