

MB SHEET Extra item -01, RA-01

Project -The Lucknow Seating D-21 Airport (Lucknow)

Sr No	Item Name	UOM	Boq Qty.	No.	Length	Width	Height	Total	Remarks
BOQ for Civil & Interior Work for LKN Dom Seating space D-21a									
1	Providing fixing testing and commissioning of braided UL Rated SS Flexible pipe With all necessary Fitting 1 Mtr. Length		8.00						
	Flexible pipe for sprinkler	nos		8.00				8.00	
	Total Qty in Nos							8.00	
	Previous bill Qty							0.00	
	This Bill Qty							8.00	✓
2	Providing and Applying kerakoll chemical Super Flex OR LATICRETE S adhesive (as per manufacturer's specification)or equivalent, inclusive of cleaning of site , and as per engineer in charge .	Sqft	405.00						
	75mm Ledge wall	Sqm		1.00	7.99		1.20	9.59	
	Seating Sides	Sqm		2.00	0.60		0.45	0.54	
	Fixed seating 2 facia	Sqm		1.00	2.25		0.37	0.83	
	Fixed seating 2 sides	Sqm		2.00	0.70		0.37	0.52	
	Seating back	Sqm		1.00	2.52	2.95		7.43	
	Less seating facia	Sqm		-1.00	2.25	0.37		-0.83	
	75mm Ledge wall	Sqm		1.00	7.98		1.18	9.42	
	Less trashbin	Sqm		-1.00	0.88		1.20	-1.06	
	Ledge Top Stone	Sqm		1.00	8.07	0.13		1.01	
	Trasbin Top	Sqm		1.00	0.91	0.45		0.41	
	High Table top	Sqm		1.00	2.15	0.45		0.97	
	High Table RHS Mirror Wall	Sqm		1.00	3.53	0.45		1.59	
	High Table top	Sqm		1.00	2.15	0.45		0.97	
	Latak	Sqm		1.00	2.15	0.08		0.16	
	High Table RHS Mirror Wall	Sqm		1.00	3.53	0.45		1.59	
	Latak	Sqm		1.00	3.53	0.08		0.26	
	Total Qty in Sqm							33.40	
	Total Qty in Sqft						10.76	359.47	
	Previous bill Qty								
	This Bill Qty							359.47	✓
3	Providing and fixing of hollow metal fire rated doors SIZE 2000 X 2400 as per IS 3614 part-1 part-2 for stability and integrity. Pressed Galvanized steel conforming to IS 277 with the following specification. Recommended fire door shall have doors tested at CBRI or ARAI for maximum rating of 2hrs. Test certificates should be available for vision lites panels as part of the fire door assembly. Door frame shall be double rebate profile of size 143 x 57 mm made out of 1.60mm (16 gauge) minimum thick galvanized steel sheet. Frames shall be Mitered and field assembled with self tabs. All provision should be mortised, drilled and tapped for receiving appropriate hardware. Rubber door silencers should be provided on the striking jamb. Frames should be	Nos	1.00						
	Fire Door	Nos		1.00				0.00	✓
	Total Qty							0.00	
	Previous bill Qty								
	This Bill Qty							0.00	
4	BWP plyboard panelling Providing and fixing of BWP plyboard paneling with necessary wooden battens with complete hardware and fixing from wall and floor	Sqft	200.24						
	Mirror Wall	Sqm		1.00	3.05	2.99		9.12	
	DB wall	Sqm		1.00	1.60	2.90		4.64	
	Less openable DB	Sqm		-1.00	1.60	0.60		-0.96	
	LHS wall	Sqm		1.00	2.00	2.00 2.80		5.80	
	Total Qty in Sqm							18.60	
	Total Qty in Sqft						10.76	200.21	
	Previous bill Qty								
	This Bill Qty							200.21	

Divesh Gargathi
11/05/24