	AJ KITCHEN						RO	
No.	AJ KITCHEN - LUCKNOW-PHE BOQ	Ticks the		Rev:		+	09.10.2023	Total
\ <u>\</u>				Date:				
A	Paris					Height	Qty	
	WATER SUPPLY PIPING CPVC PIP	Unit	Qty	Length	Width	Height		
	ER SUPPLY PUR							
	CPVC pipes conforming to ASTM D-2846, SDR-11 tees, couplars, brass, etc., suits, etc., etc., suits, etc., e					A STATE		
- 1	Brad Pes rous		-	-				
	due and CPVC solvent weld fittings like elbows, etc. suitable for (domestic and flushing) cold floor in a rated or a suitable for (domestic and flushing) cold floor in a stated or a suitable for (domestic and flushing) cold							
	stc. suitable for (domestic and flushing) like elbows, etc. suitable for (domestic and flushing) cold floor including to concealed piping within wall /							
1	fla fla (domestic and flushing) cold							
	Cap. including, concealed piping within wall /							
	chasi-							
	The shall be a shall be shall be a shall be							
	Of Int.							
- 1	deen and shaft airing in the							
- 1	directi-							
- 1	meluda - le incharga disastia a (E)							
- 1	etc.cha. The of S S serous and and I be							
-	Comest: Walls done by machine) (5					1		
	Domestic and Flushing water-Toilet internal) (Pipe shall be tested with 1.5 times working pressure as covered in specifications)							
	covered in specifications)						-	
	- Sacions)							
1	20 mm Dia							
-		R.mt	40			1		
-	For all points		10					35
-	Tap off point		35				1	3
			3				1	
	Total Qty							
	Previous Bill	P. Carlot	100 To 100 To	7		Total	Try to Sentence a les montes par year	38
	Present Bill				Carlo Control	Total		35
2	25 mm Dia	tijesta si		110 18 18 18	W. E.M.	1916131348	A THE RESERVE	3
-	32mm Dia	R.mt	0					O Grant Co.
-	40mm Dia	R.mt R.mt	0					
-	Providing 8 5:	Marie	0					
	Providing & Fixing of gun metal heavy Ball Valves-							
	PN-16 (approved makes as covered in specification) screwed type for water system of the following							
	diameters. Valve shall have with unions.							
	and one make with unions.							
	20mm Dia	Nos.	4					-
- 1	Area 1,2,3,4		4					
-							1	
	Total Qty							4
-	Previous Bill		A PROPERTY			Total	CANAL T	
	Present Bill	1771	Maria Company	The state of the s		- Grand III		
	25mm Dia	Nos.	0		F 20 5 1 6	WELL		4
	32mm Dia	Nos.	0					0
	40mm Dia	Nos.	0					4
	Providing , fixing, testing and commissioning capstan							
1	Providing , fixing, testing and commissioning capstan make Water Meter including providing & fixing							
1	transfer in clation valves strainer, non-return							
	valve,complete with an necessary manage each screwed type(15Kgs/Sq.cm). Valve shall have with							
	unian.							
		Nos						
1	20 mm Dia incoming line	Nos.	1					
-			1					
	ncoming Line		1					
	106						1	
1	Total Qty		Miles and the same			Total	1	
-	Previous Bill	No	19			14	17	1
	Present Bill 25 mm Dia incoming line	Nos.	RO	0.	net	fair pa	-17	
	25 mm Dia incoming line		RO	Du	1671	,,,		1
-	32 (1)					Well		0
					1210	12		11

mentioned capacity, suitable for 3 KG/cm2 pressure, Wall Mounted / Floor standing type, with Auto Shut- off Thermostat, along with solition Valves, Air Release valve, SS flexible connections and all other 1. St Capacity Nos. 1 Icital City Previous Bill Previous Bill Present Bill 4.3 35 L Capacity For shower Supply, installation, testing & commissioning of Stuber I year Bill 4.3 35 L Capacity For shower Supply, installation, testing & commissioning of Stuber I year Bill 4.3 35 L Capacity For shower Supply, installation, testing & commissioning of Stuber I year Bill Stub		Supply, installation, testing & commissioning of							
Mel Contest of Hose standing types with Australian Distriction of Hose standing types with Australian Distriction Assets on the Contest of Hose standing types with Australian Distriction Assets on the Contest of Hose standing types and the Contest of Hose standing the Contest of Hose standing types and the Contest of Hose standing types and the Contest of Hose standing and excepting the Contest of Hose standing and excepting the Contest of Hose standing the Contest of Hose standing the Contest o		Storage Type Electric Har and Commissioning of							
Will Mounted / Floer studies byte with Australia of Thermostal, adap with notices when is fleeting connections studied other decisions when is fleeting connections adult other decisions when is fleeting to the floeting of		mentioned capacity							
of Thermosts, alone with institution Makes, An Schools volves, Sheable connection shall other schools volves, Sheable connection shall other schools and schools volves. In Connection shall other schools are schools with the school of the sc	4	Wall Mounted (s)							
Reclass valve, St Peschle convertedow available chiefe of Company and Company		off Thomas Albert Shut-							
4. S. Capany		Rolessan Aller With isoltion Valves Air							1
5.1 St. COPACING Dotted GNy Dotted GNy Doverson Bill Instead Right Doverson Bill Supply, installationsering & commissioning of supply of the state of the s		Release valve, SS flexible connections and all other							
1. S. Capacity No. 1 Dict City Processor Commissioning of Section 1. Section		std accessories							
101 Classify 102 Classify 103 Classify 104 Classify 105 C	-	5 L Capacity-							7
Dolla Coy Dolla Coy Octobro 88 Total 1 Supply, Installarancesing & Commissioning of Supply Provided From Supply Control of Supply, Installarancesing & Commissioning & Commiss	4.2	20 L Capacity	Nos.	0.0					
India Gly Previous 80 Total Previous		τορατηγ							
Colici City Total				1		-		-	
Provide Bill 1. 31 Lispatity- for stewer Supply. Installuten, seeine & commissioning of membrane and provided special provid	THE PERSON			0		1			
1.1. SEL Capacity For shower Sepply, Installation, peoling & commissioning of shokel Type (Estric Hat Water Generator of mentioned Papers, witable for 8 KG/cm) pressure, with Auto Shurt Proposed Capacity, whatele for 8 KG/cm) pressure, with Auto Shurt Proposed Capacity, whatele for 8 KG/cm) pressure, with Auto Shurt Proposed Capacity, whatele for 8 KG/cm) pressure, with Auto Shurt Proposed Capacity, whitele showers and shore of the Auto-April 100 May 100 Ma		lotal Qty							
1.1. SEL Capacity For shower Sepply, Installation, peoling & commissioning of shokel Type (Estric Hat Water Generator of mentioned Papers, witable for 8 KG/cm) pressure, with Auto Shurt Proposed Capacity, whatele for 8 KG/cm) pressure, with Auto Shurt Proposed Capacity, whatele for 8 KG/cm) pressure, with Auto Shurt Proposed Capacity, whatele for 8 KG/cm) pressure, with Auto Shurt Proposed Capacity, whitele showers and shore of the Auto-April 100 May 100 Ma		Previous Bill		A const			Total	地位于大山市位于	
Spots (Installation, Jessing & commissioning of stockers (Installation), and the stockers of t		Present pill							
Susply, installation resting & commissioning of Shebel Type Brestic Rot. Water Generator of mentioned agreen, visible for Generator of Mentioned Floren standing type, with Australian Conference of Conference o	4.3	351.6			The second second	1.57711.00	and which the state of		
Susply, installation resting & commissioning of Shebel Type Brestic Rot. Water Generator of mentioned agreen, visible for Generator of Mentioned Floren standing type, with Australian Conference of Conference o		33 C Capacity- For shower	Nos		NATIONAL PROPERTY.	THE RESERVE	THE PARTY OF THE P		
Since of Acceptance and Control of the Control of t			1103.	RO					
Since of Acceptance and Since of Acceptance of Thermostic and Since of Acceptance and Since of Acceptance of Since of Sinc		Supply							
Since of Acceptance and Since of Acceptance of Thermostic and Since of Acceptance and Since of Acceptance of Since of Sinc		Stiphet Installation, testing & commissioning of				1			
SWAI Mounted / Pyloe standing type, with Auto Shut- Rolesse, valve, S.S. Reside connections and still other stid accessories (Optional in panty) Sit of Cos Smart 80-50 with all required accessories A Pitor to order operating and model to need to be confirmed by the Ritchen consultant) Roles of Cos Smart 80-50 with all required accessories A Pitor to order operating and model to need to be confirmed by the Ritchen consultant) Roles of Cos Smart 80-50 with all required accessories A Pitor to order operating and model to need to be confirmed by the Ritchen consultant) Roles of Cos Smart 80-50 with all required accessories A Pitor to order operating and model to need to be confirmed by the Ritchen consultant) Roles of Cos Smart 80-50 with all required accessories Confirmed by the Ritchen consultant) Roles of Cos Smart 80-50 with all required accessories A Pitor to order and be placed as per space available below the counter) Roles of Cospecity-32 Rit (10.5 US) with all required accessories of the Ritchen Consultant and Ritchen Consultant		Type Electric Hot Water Generator of				1			
off Thermoust, storing with solition valves, Air stockers, Air stockers, and accessories (Optional Is pointing). 1. 3.500 In partry-pointing. 1. 3.500 In partry-pointing. Nos. 10. STC of Eco smart RD-50 with all required accessories (Prior to order operation). STC of Eco smart RD-50 with all required accessories (Prior to order operation). Incommed by the kitchen consultant). Nos. 1 1. Total Office of the stocker of the stockers o	5	mentioned capacity suitable for 3 KG/cm2 areas				1		,	
off Thermoust, storing with solition valves, Air stockers, Air stockers, and accessories (Optional Is pointing). 1. 3.500 In partry-pointing. 1. 3.500 In partry-pointing. Nos. 10. STC of Eco smart RD-50 with all required accessories (Prior to order operation). STC of Eco smart RD-50 with all required accessories (Prior to order operation). Incommed by the kitchen consultant). Nos. 1 1. Total Office of the stocker of the stockers o	3	Wall Mounted / st				1			
Release value, S.S. Reuble connections adult other state accessories (Dipoland in pantry) 1.		off Thermost							
Site of Ecosonies (Optional in parity) 1. Site in parity spinosi 2. Site in parity spinosi 3. Site in parity spinosi 3. Site of Ecosonies (Optional in parity) 3. Site of Ecosonies (South all required accessories (A Prior to order specialty and model to need to be confirmed by the kitchen consultant) 3. Site of Ecosonies (South all required accessories (A Prior to order specialty and model to need to be confirmed by the kitchen consultant) 3. RO: 4. Prior to order specialty and model to need to be confirmed by the kitchen consultant) 5. RO: 5. Total Gly 6. Previous Bill 7. Previous Bill 8. Silic of AcO grease trap-model Lipumbbil 0.3 5. Silic of AcO grease trap-model Lipumbbil 0.3 6. Capacity -23 lint (0.5 LPS) with all required available below the counter) 5. Silic of AcO grease trap-model Lipumbbil 0.3 6. Capacity -23 lint (0.5 LPS) with all required available below the counter) 7. Silic of AcO grease trap-model Lipumbbil 0.3 8. Capacity -23 lint (0.5 LPS) with all required available placed as personal placed by previous Bill 9. South districts of the placed as personal placed by previous Bill 9. South districts of the placed as personal placed by previous Bill 10. South districts of the placed as personal placed by previous Bill 10. South districts of the placed as personal placed by previous Bill 10. South districts of the placed as personal placed by previous Bill placed by and the placed by and the placed as personal placed by and the placed by and the placed as personal placed by and the placed by and th		Release val.							
5.1 Stor in parity: potional Nos. 80 3.3 10sw 3ph. subject to load permits Nos. 80 STC of Eco smart RO-50 with all required accessories (Prior to order openity and model to need to be confirmed by the kitchen consultant) 8 RO. 0 1 Total City Frevious Bill Prosent Bill STC of ACO greate trap-model Upumobil 0.8- Capacity -48 lit (0.8 LPS) with all required accessories (order stable be placed as per space available below the counter) STC of ACO greate trap-model Upumobil S. Capacity -48 lit (0.8 LPS) with all required accessories (order stable be placed as per space available below the counter) STC of ACO greate trap-model Upumobil S. Capacity -42 lit (0.5 LPS) with all required accessories (order stable below the counter) a Grease trap 0 Total Total City Frevious Bill Prosent Bill B ORANAGE Total City Conforming to 15 13592/92 and agri type prise above 100 mm of the conforming to 15 13592/92 including fittings conforming to 15 13592/92 including fittings conforming to 15 13592/92 including things post to required length, lyving in the post time to required and and level, noming, supporting with PVC chall but deep galvanced water accessions to required spaces and level, noming, supporting with PVC chall but deep galvanced water accessing the space of the conforming to 15 13592/92 including things conforming to 15 13592/92 including things post to the galvanced water accessing the space of the conforming to 15 13592/92 including things conforming to 15		std acceptable connections and all other							
Solve in pantry, opinional Nos. No. Nos. 1 1 18W-3ph subject to load permits Nos. 80 N	_	accessories (Optional in pantry)							
Sitt of Eco smart RD-50 with all required accessories and Prior to order opacity and model to need to be confirmed by the kitchen consultant) A RD- Total City Previous Bill Prevent ABIR (a pre) with all required accessories and provided the provided Bill Prevent Bill STC of ACO grease trap-model Lipumobil 0.8-consultant (a previous Bill Prevent Bill (a pre) with all required accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space accessories). Support of the provided by the order of the placed and space and beet, printing, apporting with PVC challed and sincested (Die Ball before and sincested (Die Bal	5.1	3.5kw in							
Sitt of Eco smart RD-50 with all required accessories and Prior to order opacity and model to need to be confirmed by the kitchen consultant) A RD- Total City Previous Bill Prevent ABIR (a pre) with all required accessories and provided the provided Bill Prevent Bill STC of ACO grease trap-model Lipumobil 0.8-consultant (a previous Bill Prevent Bill (a pre) with all required accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space available below the counter accessories (Order shall be placed as per space accessories). Support of the provided by the order of the placed and space and beet, printing, apporting with PVC challed and sincested (Die Ball before and sincested (Die Bal	5.2	Sky,	Noc						
STC of Eco mart RO-So with all required accessories (Prior to order operalty and model to need to be confirmed by the kitcher consultant) STC of Eco mart RO-So with all required accessories (Prior to order operalty and model to need to be confirmed by the kitcher consultant) Nos 1 SO-O Octol City Previous Bill Prosent Bill STC of ACO grease trap-model Lipumobil O.B. Capacity -48 lift (.0 LPS) with all required accessories (Order shall be loaded by the counter) STC of ACO grease trap-model Lipumobil S. Capacity -28 lift (.0 LPS) with all required accessories (Order shall be loaded by the counter) STC of ACO grease trap-model Lipumobil S. Capacity -28 lift (.0 S. IPS) with all required accessories (Order shall be loaded by the counter) Total Oly Provious Bill Prozont Bill Prozont Bill Prozont Bill DRAINAGE Lapticy SVW pubs. conforming to 15-13937/92 and agri type pups above 100 rm disc conforming to 15-19357/92 including fittings conforming to 15-19357/93 and agri type pups above 100 rm disc conforming to 15-19357/93 including fittings conforming to 15-19357/	_			RO				ļ	
SITC of Eco smart RO, 50 with all required accessories I Prior to order cpacetity and model to need to be confirmed by the kitchen consultant) 8 RO. 0 O 1 Iolid Clyy Previous Bill Prosent Bill Bill Prosent Bill Prosent Bill Bill Prosent Bill Bill Bill Bill Bill Bill Bill Bil	٥.٥	13kw-3ph- Subject to Lond	Nos.	RO					
SITC of Eco smart RO, 50 with all required accessories I Prior to order cpacetity and model to need to be confirmed by the kitchen consultant) 8 RO. 0 O 1 Iolid Clyy Previous Bill Prosent Bill Bill Prosent Bill Prosent Bill Bill Prosent Bill Bill Bill Bill Bill Bill Bill Bil		- doject to load permits	Nos.						
confirmed by the Kitchen consultant) Nos 1 AQUATION STATE AND ST									
confirmed by the Kitchen consultant) Nos 1 AQUATION STATE AND ST		SITC					-		
confirmed by the Kitchen consultant) Nos 1 AQUATION STATE AND ST		of Eco smart RO-SO with all services							
confirmed by the Kitchen consultant) Nos 1 AQUATION STATE AND ST		(Prior to order co-							
A RO- Total Qly Previous Bill Present Bill STC of ACO grease trap -model Upumobil 0.8- Capacity -48 Bit (0.8 LPS) with all required accessories (Order shall be placed as per space available below the counter) STC of ACO grease trap -model Upumobil 5 - Capacity -32 Bit (0.5 LPS) with all required accessories (Total Qly Previous Bill Present Bill B DRAINAGE DPVC-SYR piecs conforming to IS 13592/92 including fittings conforming to IS 14935/99 and agri type papes above 100 mm dia, conforming to IS 1995, wwng in the position to required grade and level, juniting, supporting with PVC claribut deep palvansed bracket to the deep palvansed bracket to the own of the palvansed bracket to the own of th		confirmed but he is a					1		
a RQ- Intol QIy Previous Bill Prosent Bill SiT C of ACO grease trap-model Lipumobil o.8 - Capacity -48 lit (0.8 LPS) with all required accessories (Order shall be placed as per space available below the counter) SiTC of ACO grease trap-model Lipumobil S - Capacity -32 lit (0.5 LPS) with all required accessories Grease trap O Total Oly Previous Bill Prosent Bill Present Bill Bill Bill Bill Bill Bill Bill Bill	6	the kitchen consultant)					1		
a RO- loted QPy Previous Bill Present Bill STIC of ACO grease trap-model Upumobil D.B. Capacity -48 lit (0.8 LPS) with all required accessories (Order shall be placed as per space available below the counter) STIC of ACO grease trap-model Upumobil S - Capacity -32 lit (0.5 LPS) with all required accessories (Order shall be placed as per space available below the counter) STIC of ACO grease trap-model Upumobil S - Capacity -32 lit (0.5 LPS) with all required accessories Grease trap O Total Oly Previous Bill Present Bill B Present Bill Capacity - Capacit		·	NI						
Total Oly Previous Bill Forsent Bill SITC of ACO grease trap -model Lipumobil 0.8- 7 Capacity -48 lit (0.8 LPS) with all required accessings (Order shall be placed as per space available below the counter) SITC of ACO grease trap -model Lipumobil 5. 8 Capacity -32 lit (0.5 LPS) with all required accessings (Order shall be placed as per space available below the counter) SITC of ACO grease trap -model Lipumobil 5. 9 Capacity -32 lit (0.5 LPS) with all required notes accessing a constraint of the provided accessing to the provided a			NOS	1			1		
Total Previous Bill Present Bill SITC of ACO grease trap -model Lipumobil 0.8- 7 Capacity -48 lit (0.8 LPS) with all required accessings (Order shall be placed as per space available below the counter) SITC of ACO grease trap -model tipumobil 5. Capacity -32 lit (0.5 LPS) with all required accessings (Order shall be placed as per space available below the counter) SITC of ACO grease trap -model tipumobil 5. Capacity -32 lit (0.5 LPS) with all required Nos 1 Freshous Bill Present Bill Bill Present Bill Bill Present Bill Present Bill Bill Present Bill Bill Present Bill Bill Present Bill Bill Bill Bill Bill Bill Bill Bil							1		
Total Previous Bill Present Bill SITC of ACO grease trap -model Lipumobil 0.8- 7 Capacity -48 lit (0.8 LPS) with all required accessings (Order shall be placed as per space available below the counter) SITC of ACO grease trap -model tipumobil 5. Capacity -32 lit (0.5 LPS) with all required accessings (Order shall be placed as per space available below the counter) SITC of ACO grease trap -model tipumobil 5. Capacity -32 lit (0.5 LPS) with all required Nos 1 Freshous Bill Present Bill Bill Present Bill Bill Present Bill Present Bill Bill Present Bill Bill Present Bill Bill Present Bill Bill Bill Bill Bill Bill Bill Bil									
Total Previous Bill Present Bill SITC of ACO grease trap -model Lipumobil 0.8- 7 Capacity -48 lit (0.8 LPS) with all required accessings (Order shall be placed as per space available below the counter) SITC of ACO grease trap -model tipumobil 5. Capacity -32 lit (0.5 LPS) with all required accessings (Order shall be placed as per space available below the counter) SITC of ACO grease trap -model tipumobil 5. Capacity -32 lit (0.5 LPS) with all required Nos 1 Freshous Bill Present Bill Bill Present Bill Bill Present Bill Present Bill Bill Present Bill Bill Present Bill Bill Present Bill Bill Bill Bill Bill Bill Bill Bil	а	P.O.							
Total Oly Previous Bill Present Bill SITC of ACO grease trap-model Lipumobil 0.8 - Capacity - 48 lit (0.8 LPS) with all required accessories (Order shall be placed as per space available below the counter) SITC of ACO grease trap-model Lipumobil 5 - Capacity - 32 lit (0.5 LPS) with all required accessories SITC of ACO grease trap-model Lipumobil 5 - Capacity - 32 lit (0.5 LPS) with all required accessories Grease trap O Total Previous Bill Present Bill B DRAINAGE upvC-SVW pipes conforming to 15: 13932/92 including fittings conforming to 15: 14935/99 and agri type pipes above 100 mm dia. conforming to 15: 4985, cutting the pipes to required lengths, laying in- the position to required garde and level, inning, supporting with PVC cleat hot deep galvansed bracket support, but deep galvansed or bracket support, but deep galvansed when the content on the content counts, anchor fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shaft / supported on wall / fund pellow slab et with all material & labor complete and as directed. [The Rate shall include supply and fraing of hording plansansed bracket nut bolity PVC Coated U Clamp and screws] Vertical line bracket shall be fixed at every O Bint to 1.00 mt.; [for Soil, Waste, Vent and RVVP-Internal and vertical shaft).		NU-							
Present Bill SITC of ACO grease trap -model Lipumobil 0.8 - Capacity -48 lit (0.8 LPS) with all required accessories (Order shall be placed as per space available below the counter) SITC of ACO grease trap -model Lipumobil 5 - Capacity -32 lit (0.5 LPS) with all required accessories Grease trap 0 Total Oly Previous Bill Somannage upvC-SWR pipes conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS- 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC chathort deep galvanised bracket supports, hot deep galvanised inti-bolts, anctor fastiers, PVC coated U-clamp, resting and rectifying leakages for piping within vertical shafts / supported on valif / hung below slab etc. with all material 8 Lister complete and as directed. [The Rate shall include supply and fixing of hoteling galvanised bracket nut botty PVC Coated U-Clamp, resting and rectifying leakages for piping within vertical shafts / supported on valif / hung below slab etc. with all material 8 Lister complete and as directed. [The Rate shall include supply and fixing of hoteling galvanised bracket nut botty PVC Coated U-Clamp and screws) Vertical line bracket shall be fixed at every 0.8 mit to 1.00 mtr.] (for Soil, Woste, Vent and RWP-loternal and vertical shaft).				0				-	
Previous Bill SITC of ACO grease trap -model Lipumobil 0.8 - Capacity -48 lit (0.8 LPS) with all required accessories (Order shall be placed as per space available below the counter) SITC of ACO grease trap -model Lipumobil 5 - Capacity -32 lit (0.5 LPS) with all required accessories Grease trap 0 Total Oly Previous Bill SomanAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS 14935/99 and agri type pipes above 100 mm dia. conforming to IS 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised mut-bolts, anchor fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shaft y supported on wall / hung below slab etc with all material & labor complete and as directed. [The Rate shall include supply and flow of hot hot galvanised bracket nut botts / PVC Coated U Clamp, testing and rectifying leakages for piping within vertical shaft y supported on wall / hung below slab etc with all material & labor complete and as directed. [The Rate shall include supply and flow of hot hot galvanised bracket nut botts / PVC Coated U Clamp, and screws) Vertical line bracket shall be fixed at every Six to to 1.00 mtr.] (for Soil, Waste, Vent and RWP-internal and vertical shaft).									
Previous Bill SITC of ACO grease trap -model Lipumobil 0.8 - Capacity -48 lit (0.8 LPS) with all required accessories (Order shall be placed as per space available below the counter) SITC of ACO grease trap -model Lipumobil 5 - Capacity -32 lit (0.5 LPS) with all required accessories Grease trap 0 Total Oly Previous Bill SomanAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS 14935/99 and agri type pipes above 100 mm dia. conforming to IS 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised mut-bolts, anchor fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shaft y supported on wall / hung below slab etc with all material & labor complete and as directed. [The Rate shall include supply and flow of hot hot galvanised bracket nut botts / PVC Coated U Clamp, testing and rectifying leakages for piping within vertical shaft y supported on wall / hung below slab etc with all material & labor complete and as directed. [The Rate shall include supply and flow of hot hot galvanised bracket nut botts / PVC Coated U Clamp, and screws) Vertical line bracket shall be fixed at every Six to to 1.00 mtr.] (for Soil, Waste, Vent and RWP-internal and vertical shaft).	100	Total Oty						-	
Prosent 691 SITC of ACO grease trap-model Lipumobil 0.8 - Capacity -48 lit (0.8 LPS) with all required accessories (Order shall be placed as per space available below the counter) SITC of ACO grease trap-model Lipumobil 5 - Capacity -32 lit (0.5 LPS) with all required accessories Grease trap O Total Previous 8:II Present Bill B DRAINAGE pPV-SVR pipes conforming to IS 13592/92 including fittings conforming to IS 14935/99 and agritype pipes above 100 mm dia. conforming to IS; 4985, cutting the pipes to required length, laying in the position to required grade and level, jointing, supporting with PVC clear, but deep galvansed above bracket supports, but deep galvansed aut-bots, anchor fastners, PVC coated U clamp, testing and recttyfrig leakages for pipe gain with pVC clear, but deep galvansed aut-bots, anchor fastners, PVC coated U clamp, testing and recttyfrig leakages for pipe gain with pVC clear to U clamp, testing and bracket supports, but deep galvansed brackets and include supply and fixing of hording palvansed bracket not botty PVC Coated U Clamp and screws] Vertical line bracket shall be freed a revery 8 mm to 0 1.00 mm.) (For Soil , Waste, Vent and RWP-Internal and vertical shaft).			WARLENT	1 Horas Par	Section by the second section is	Late Office and on the	240000000000000000000000000000000000000		
SITC of ACO grease trap - model Lipumobil 0.8 - Capacity - 48 (1 (0.8 LPS) with all required accessories () Order shall be placed as per space available below the counter) SITC of ACO grease trap - model Lipumobil 5 - Capacity - 32 lit (0.5 LPS) with all required accessories SITC of ACO grease trap - model Lipumobil 5 - Capacity - 32 lit (0.5 LPS) with all required accessories a Grease trap 0 0 1 Total Present Bill Bill Present Bill Bill Bill Bill Bill Bill Bill Bil	tion For the	Previous Bill	THE PERSON NAMED IN	100000000000000000000000000000000000000	Crear Rolling Section	A DESCRIPTION	Total		
Total Cly Previous Bil Prosent Bil DRAINGE UPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC clast but deep galvansed bracket supports, but deep galvansed bracket support but on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvansed bracket nut botis/ PVC. Coated U -Clamp, testing and rectifying leakages for pping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvansed bracket nut botis/ PVC. Coated U -Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mit to 1.00 mit.] (for Soil , Waste, Vent and RWP-Internal and vertical shaft).	以及 其	Present Bill	Action Co.						
7 Capacity -48 lif (0.8 LPS) with all required accessories (Order shall be placed as per space available below the counter) SITC of ACO grease trap-model Lipumobil S - Capacity -32 lif (0.5 LPS) with all required Nos 1 accessories a Grease trap 0 0 Total Cly Previous Bill Previous Bill Prosent Bill VPC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS 14933/99 and agri type pipes above 100 mm dia conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat hot deep galvanised bracket supports, hot deep galvanised mut-polits, annihor fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut botic/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mit to 1.00 mt.] (for Soil , Waste, Vent and RWP-Internal and vertical shaft).		SITC of ACO grease trap model in the	Mary Company C	7 923		TO MAKE	A THE WHITE	Date of the same	STATE OF THE PARTY
accessories (Order shall be placed as per space available below the counter) SITC of ACO grease trap -model Lipumobil S - Capacity -32 lit (0.5 LPS) with all required accessories a Grease trap		Canacity 48 lit 40 a rest					THE RESERVED OF	Serious Constitution	
a SITC of ACO grease trap -model Lipumobil 5 - Capacity -32 lit (0.5 IPS) with all required accessories a Grease trap 0 Total Oly Previous Bill Present Bill B DRAINAGE UPVC-SVIR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agritype pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying inthe postition to required grade and level, jointing, supporting with PVC cleat, hot deep galvansed bracket supports, hot deep galvansed out-bolts, annother fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [I he Rate shall include supply and fixing of hotding galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be freed at every 0.8 mt to 1.00 mtr.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft.).	7	oapacity 48 iit (0.8 LPS) with all required				1			
a SITC of ACO grease trap -model Lipumobil 5 - Capacity -32 lit (0.5 IPS) with all required accessories a Grease trap 0 Total Oly Previous Bill Present Bill B DRAINAGE UPVC-SVIR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agritype pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying inthe postition to required grade and level, jointing, supporting with PVC cleat, hot deep galvansed bracket supports, hot deep galvansed out-bolts, annother fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [I he Rate shall include supply and fixing of hotding galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be freed at every 0.8 mt to 1.00 mtr.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft.).		accessories (Order shall be placed as per space	Nos	0					
a Grease trap 0 Total Oly Previous Bill Prosent Bill B DRAINAGE upVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, but deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hurg below slab etc with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolty PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft).		available below the counter)				1			
a Grease trap 0 Total Oly Previous Bill Prosent Bill B DRAINAGE upVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, but deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hurg below slab etc with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolty PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft).									
a Grease trap 0 Total Oly Previous Bill Prosent Bill B DRAINAGE upVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, but deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hurg below slab etc with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolty PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft).		SITC of ACO grease tran-model Linumobil s							
a Grease trap 0 Total Oly Previous Bill Present Bill B DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS 14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, but deep galvanised bracket supports, but deep galvanised nut-botts, anchor fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fizing of hotdip galvanised bracket nut bottly PVC Coated U-Clamp and screws) Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft.).	8	Capacity 23 lit (0.5 lpc)					-		
a Grease trap 1 Total Oly Previous Bill Present Bill B DRAINAGE upvC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PvC cleat, that deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PvC coated U clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below dab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolty PvC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft.).	0		Nos	1					
Total Oly Previous Bill Prosent Bill B DRAINAGE upVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (for Soil , Waste, Vent and RWP-Internal and vertical shaft).		accessories		_					
Total Oly Previous Bill Prosent Bill B DRAINAGE upVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (for Soil , Waste, Vent and RWP-Internal and vertical shaft).									
Total Oly Previous Bill Prosent Bill B DRAINAGE upVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (for Soil , Waste, Vent and RWP-Internal and vertical shaft).									
Total Oly Previous Bill Present Bill B DRAINAGE upVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying inthe position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-clamp and screws] Vertical line bracket shall be fixed at every 0.8 mt to 1.00 mtc.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft.).	a	Grease trap							
Total Oly Previous Bill Present Bill B DRAINAGE upVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying inthe position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-clamp and screws] Vertical line bracket shall be fixed at every 0.8 mt to 1.00 mtc.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft.).	а	Grease trap		0					
Present Bill B DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleathot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft).	а	Grease trap		0					
Present Bill B DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleathot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below stab etc with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft).	а	Grease trap		0					
Present Bill B DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleathot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below stab etc with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft).	а	Grease trap		0				-	
Present Bill B DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft).	a			0					
DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying inthe position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1,00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).	а	Total Qly		0			Total	-	
uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised obracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).	3	Total Qly Previous Bill		0			Total	-	
including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).		Total Qly Previous Bill Present Bill		0			Total		
including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).		Total Qly Previous Bill Present Bill		0			Total		
type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).		Total QIy Previous Bill Present Bill DRAINAGE		0			Total		
4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).		Total QIy Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92		0			Total		
the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to: 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).		Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri		0			Total		
supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U. clamp, testing and rectifying leakages for piping within vertical shafts. / supported on wall / hung below slab. etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft.).		Total QIy Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS:		0			Total		
supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U. clamp, testing and rectifying leakages for piping within vertical shafts. / supported on wall / hung below slab. etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft.).		Total QIy Previous Bill Present Bill DRAINAGE upVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in		0			Total		
bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdlp galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).		Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing,		0			Total		
anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotding palvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).		Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing,		0			Total		
rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotding palvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).		Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised		0			Total		
supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).		Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts,		0			Total		
supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).		Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and		0			Total		
material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to: 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).	В	Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U clamp, testing and pertifying leakages for piping within vertical shafts.		0			Total		
shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to: 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).	В	Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all		0			Total		
bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft). Divertical shaft).	В	Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all		0			Total		
Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft). Buy	В	Total QIy Previous Bill Present Bill DRAINAGE upVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat,hot deep galvanised bracket supports,hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate		0			Total		
Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft). Buy	В	Total Oly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdig galvanised		0			Total		
1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft). Divert	В	Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in - the position to required grade and level, jointing, supporting with PVC cleat,hot deep galvanised bracket supports,hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdlp galvanised bracket nut bolts/ PVC Coated U-Clamp and screws]		0			Total		
and vertical shaft). Divest Jaibally (124)	В	Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to		0			Total		
and vertical shart). Divest Suibally 1.1 40mm Dia R.mt 2 TH ab 24	В	Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to		0			Total		
1.1 40mm Dia R.mt 2 11106 24	В	Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal		0					
1.1 40mm Dia R.mt 2 11106 24	В	Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal		0					
1.1 40mm Dia R.mt 2	В	Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal		0	The state of the s	nod.			
1.1 40mm Die	В	Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal		0	0	vest			
1 VIII	1	Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdig galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).	R.mi		<i>D</i>	vest			
	1	Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdig galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).	R.mt		0	vest			
	1	Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdig galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).	R.mt	2	<i>D</i> :	vest			
a Main header 2	1 1.1	Total QIy Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).	R.mt	2	0	vest			
a Main header 2	1 1.1	Total QIy Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).	R.mt	2	<i>D</i>	vest Tu			
I I I I TWALE	В	Total Qly Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal		0					
	B 1	Total QIy Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).	R.mt	2	0	vest			
a Main header 2	1 1.1	Total QIy Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdip galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to 1.00 mtr.] (For Soil , Waste, Vent and RWP-Internal and vertical shaft).	R.mt	2	0	vest Tu			
a Main header 2 Total Qfy	1 1.1	Total QIy Previous Bill Present Bill DRAINAGE uPVC-SWR pipes conforming to IS 13592/92 including fittings conforming to IS-14935/99 and agri type pipes above 100 mm dia. conforming to IS: 4985, cutting the pipes to required lengths, laying in- the position to required grade and level, jointing, supporting with PVC cleat, hot deep galvanised bracket supports, hot deep galvanised nut-bolts, anchor fastners, PVC coated U-clamp, testing and rectifying leakages for piping within vertical shafts / supported on wall / hung below slab etc. with all material & labor complete and as directed. [The Rate shall include supply and fixing of hotdlp galvanised bracket nut bolts/ PVC Coated U-Clamp and screws] Vertical line bracket shall be fixed at every 0.8 mtr to: 1.00 mtr.] (For Soil, Waste, Vent and RWP-Internal and vertical shaft.). 40mm Dia	R.mt	2	0	vest			

	Previous Bill				And the second s	Mary Control of the C	and a second second second
A LA	Present 8M				The same of the sa	The Control of Control of the Contro	and the second s
.2	50mm Dia	R.mt	8			Control and the control of the second of the control of the contro	and the state of the same of the same of the state of the state of the same of
						And the same of th	and the state of t
3	To- Tap- off points		7			The same of the sa	AND THE PROPERTY OF THE PROPER
		-				The second secon	A CONTRACT OF THE PARTY OF THE
WHY.	Total Qty	-			Total	and the American Company of the Comp	and the second s
-	Previous Bill						The second of th
	Present Bill	0			And the second s	The second section of the sect	The second secon
1.3	65mm Dia	R.mt	0				The second secon
1.4	75mm Dia	R.mt	10				The second secon
						1	And the second of the second o
a	To tap off points		15			The second secon	and the same of th
		_			Total	and the second s	A CONTRACTOR OF THE PROPERTY OF THE PARTY OF
	Total Qty				Total		And the second of the second o
	Previous Bill						and the second s
	Present Bill	R.mt	-				
5	100 mm Dia		5				
			1			1	
9	To tap off points		4				The state of the s
							200000000000000000000000000000000000000
SYDE A	Total Qty			THE STATE OF THE S	Total		
	Previous Bill		1000		1.0.01	-	
Ten	Present Bill						
.6	150 mm Dia	R.mt	RO				
	July Dig		NO				_
	Supply, Install PVC Floor Trap for the following						
	pipes including making all approved quality Solvent						
2	cement joints with material & labour etc. all						
	complete as per direction of the engineer-in-charge.						
		Nos.	2	1,250			
1	Floor Trap					2	
10.0	Total Qty		1 6 4 3 4	THE STATE OF THE S	Total		
Virta.	Previous Bill						
	Present Bill Supply, Install PVC Multi Floor Trap for the	4-1			SANTA POLICIANA		
	following pipes including making all approved quality						
3	Solvent cement joints with material & labour etc.						
	all complete as per direction of the engineer-in-						
	charge.	Nos.	5				
а	Floor trap					5	5
	Total Qty	Parkey	42,190	14 Tr	Total	HE THE STATE OF THE	5
_	Previous Bill						C
2	Present Bill	17 H. W. 1	Port Title		HARVE THE SE		5
	Supply, Install PVC urinal Traps including fixing with necessary consumables with Circular SS Grating with						
4	anti cockroach jali Suitable for 75mm Dia outlet	Nos.					
	, so outet		0				
			0				
	Supply, Install PVC P- Traps including fixing with						
5	necessary consumables with Circular SS Grating with	Nos.					
_	anti cockroach jali Suitable for 75mm Dia outlet	1103.					
			0				
С	SANITARY AND C. P. FITTINGS & FIXTURES		in Joyana	STREET STREET			
	Only installation, testing and commissioning of			14		建工工工工工工工工	A CANADA A
	sanitary and C.P. fittings						
					PROPERTY NO.		STEEL STEEL STEEL
.1	EWC with seat cover	Nos	0				
.2	Concealed flush tank	Nos	0				
.3	Concealed flush valve	Nos	0				
.4	Health Faucet 2 Way Bib-Cock with connection for Health Faucet	Nos	0				
.5	Z yvay bib-cock with connection for health raucet	Nos	0				
.6	Bided	Nos	R.O.				
. 7	Under Counter Wash Basin including waste Coupling						
. ,		Nos	0				
8	Wash Basin Cock	Nos	0				
.9	shower and mixer	Nos .	0		vest Jaiper	h-	
.10	Jet Spray	Nos	0		191161		
11	Bath Tublincluding waste Coupling and nessessary	Nos	0	Di	1011		
	Connections Under Counter Sink including waste Coupling	Nos	2		4/0/14	,	
		No.	2		TO TO THE		

1	and the second													
1					_									
1						-								0
			7	-				_				AC. 12 (18)		0
		Total Qty Previous Bill				40	P. L. Barre	23.00	Burgh.	Total	(S. 12) 7 PAGE		2:0	50
		Present Bill	100		-			Start Start I	-	a subjective	in the Other			
	1,13	Sink Pillar Cock		Nos	_	2	5 7 1							-
														1
					_									3
	1001-100-100	To be light	100		-					T-1-1	and the least the life	The street		2
		Total Qty Previous Bill			ALL DAVID	28,49		17 60		Total	100			7
	981777132	D	MA CO		N. Harris	10000	107A L 1025	DEED TO SEE		at Atto	17 472 HAZ	(100 H) (100 H)		-
	1.14	Bottle Trap for WHB/ sink and urinal with all		Nos		T. IS.								\Box
- 1		connecting pipes				2								
-			-		-									
-	Our State of		10 10 12	The design	-				-	27.1	CO CALLEST NICES	gran Vill		0
-		Total Qly Previous Bill			-	Service St	THE REAL PROPERTY.		20.00	otal	A Company of the Company	0.11.10.10		0
		Present Bill		THE R		Charles Bush			5-K5N 1			No late	7.1	00
		ngle Cock with PVC pipe connection upto		Mari	-	David Har		Dec Calvarian						-
	W	/HB/sink/Geyser connection		Nos	7									-
_						+								7
	-											Walter A. of Chapter	13117121111111111111	0
		lal Qly		14138	4			4 表示。	Te	otal .	S PROPERTY OF	Klarenka		7
		evious Bill									3 10.000 1000 1000		111111111111111111111111111111111111111	-
1	1.16 Urii	esent Bill		No	1		New York		SE L					\dashv
		nai o Flush Valve & Sensor with connecting pipin	28	Nos	0			-	-		-			
1	1	eader for urinal(DC)	g a	Nos	0									-
	15516	ioi armai(DC)	-			-		+						\dashv
						-		-	_		-		-A (1) (1) (1) (1)	
	SUB	TOTAL -C-SANITARY AND C. P. FITTINGS &			No. of the Last	San Spelan	1. 4.5.	2 - 2 - 3 2	nivi o	1 Wash				
	FIXT	JRES (ONLY INSTALLATIONS)											202 11 22 22	-
					(min 1) (1) (1)	ACT NOT SEE		4 10 30 17 4 1		7-4-8-387-10	THE PROPERTY OF THE PARTY OF TH		5.0578 (275)	100
D		RATING	1 77	11288	out of the		01-71-05-71	1 (37)(3)(4)	Cata Sad	SHEET.	1988230		建设是一个大学	-
	Only i	nstallations/ testing and commissioning of									Secretary.	STATE		
	S.S.Gr	atings												
														\dashv
1	16 swg Frame a frame v	te for S.S Grating size, 1200mm x 200mm, 25mm x25mm Square Pipe around the and 20mmX 20mm Square pipe in center ovith SS perforated tray (304 SWR). Complet rehitectural detail drawing & Site Engineer' on.	of No	os.	0									
	tiling etc 16 swg 25 Frame an frame wit	hamber in brick work including internal for S.S Grating size, 600mm x 300mm, in imm x25mm Square Pipe around the d 20mmX 20mm Square pipe in center of h SS perforated tray (304 SWR). Complete nitectural detail drawing & Site Engineer's		5.	2									-
												\rightarrow		
T	otal Qty		contact water	Miles I Apartic to		S-6-72-1	Control Control	No. 1971				-		
	revious Bil	CONTROL OF THE SECOND STATE OF THE SECOND STAT				ENA 15		F 6 6	Tota		为我们到了	SEPTE I	Alexander and a second	
	resent Bill		organi Siza	1007 1750	Grand Gr	California and California	SC 41/2002	Voltage and				-		
111	C3CIII DIII	ang Mulataya Matari-Mulayuri Pina Alicu, manda Ali Basin ang Salata ang Salataya	4 4 4	1777 B. J.					3 200		2011年17年2		A CONTRACTOR OF THE PARTY OF TH	0
tilli 16 Fran fran as p	ng etc for swg 25mn me and 2 ne with SS	nber in brick work including internal S.S Grating size, 300mm x 300mm, in n x25mm Square Pipe around the 10mmX 20mm Square pipe in center of 1 perforated tray (304 SWR). Complete ctural detail drawing & Site Engineer's	Nos.		1								·	0
				-										
-				_						-				
-										-				1
									1	-				1
Total	Qty					MU 197	ALC:		Total			+		1
Previo	ous Bill			-	C. Comp.					-		See 1		
Preser	nt Bill	The state of the s					1	(d)	50	B		-		
						W.	10CF	13	tha		The state of the	100		
						N.	an,	110	110					70
							"	100	M					70
							14							57

5	Making chamber in brick work including internal tiling etc for S.S. Grating size, 300mm x 300mm, in 16 swg 25mm x25mm Square Pipe around the Frame and 20mmX 20mm Square pipe in center of frame with SS non perforated tray (304 SWR). Complete as per architectural detail drawing & Site Engineer's instruction.	Nos.	1				
	Total Qty Previous Bill			10-11-11-11-11-11-11-11-11-11-11-11-11-1	Total		
	Present Bill				Total		
	NOTES:			5 1 1 10	La constant	per les de la Trada	
	Taxes and duties shall be Extra as actual						
	2. Supply and installation of Sanitary fixtures and fitting in th kitchen and toilets						
	3. Supply of S.S. gratings in kitchen						

Dived Toilbathi