


Sl. No.	Item Code	Item Name	Item Description	UOM	Qty	Unit Price	Amount	Work Done %	RA Amount	Amount
1		PR for Civil & Interior Work	PR for Civil & Interior Work	NOS	1.000					1499.71
2	a.1	Dismantling and Demolitions	Dismantling and Demolitions							
3	a.1	Dismantling the existing flooring, ceiling, walls, partition, fixed loose furniture, toilets, pantry, etc. Cost to include carting away all debris from site, lead and lifts, material, labour, transportation and all other incidental charges etc.	Dismantling the existing flooring, ceiling, walls, partition, fixed loose furniture, toilets, pantry, etc. Cost to include carting away all debris from site, lead and lifts, material, labour,							
4	a.2	Brick Wall, Wall tiles, Sinter tiles, including base, Partitions, Existing Wall Plaster, Electrical	Brick Wall, Wall tiles, Sinter tiles, including base, Partitions, Existing Wall Plaster, Electrical	Sq.ft	378.750	55.00	20831.25	0%	0	20831.25
5	a.3	Removal PCC of thickness upto 5 inches	Removal PCC of thickness upto 5 inches	Sq.ft	0.000	0.00	0		0	0
6	a.4	Removal PCC of thickness between 6 inches to 12 inches	Removal PCC of thickness between 6 inches to 12 inches	Sq.ft	0.000	0.00	0		0	0
7	a.5	False ceiling removing inclusive wire, light	False ceiling removing inclusive wire, light	Sq.ft	0.000	0.00	0		0	0
8	a.6	Facade (Including Glass, Signage, Window Frames and ACP boxing etc)	Facade (Including Glass, Signage, Window Frames and ACP boxing etc)	Sq.ft	0.000	0.00	0		0	0
9	a.7	Existing Rolling shutter removing	Existing Rolling shutter removing	Sq.ft	0.000	0.00	0		0	0
10	a.8	Existing Cable Trays, Duct Removing from the site and carting away from the site	Existing Cable Trays, Duct Removing from the site and carting away from the site	Sq.ft	0.000	0.00	0		0	0
11	b.1	Making Core cut with Diamond cutter clearing the debris and carting away the same from site.	Making Core cut with Diamond cutter clearing the debris and carting away the same from site.							
12	b.2	Making core cutting of 75 dia	Making core cutting of 75 dia	Nos.	0.000	0.00	0		0	0
13	b.3	Making core cutting of 100 dia	Making core cutting of 100 dia	Nos.	0.000	0.00	0		0	0
14	b.4	Making core cutting of 150 dia	Making core cutting of 150 dia	Nos.	0.000	0.00	0		0	0
15	c	Making core cutting of 200 dia	Making core cutting of 200 dia	Nos.	0.000	0.00	0		0	0
16		Making cutouts and openings in existing walls for ducts etc. The cost to be inclusive of making good all affected areas with smooth plaster and disposal of debris at an indicated location off site.	existing walls for ducts etc. The cost to be inclusive of making good all affected areas with smooth plaster and disposal of debris at an indicated	Nos.	0.000	0.00	0		0	0
17	a	RCC and PCC	RCC and PCC							
18	b	Providing Laying Main cement concrete specified grade (M10) including the cost of centering and shuttering, required curing. Approved make cement is PPC (ACC, Ultra tech, Birla)	Providing Laying Main cement concrete specified grade (M10) including the cost of centering and shuttering, required curing. Approved make cement is PPC (ACC, Ultra tech, Birla)	cuft	238.520	425.00	101371	70%	91233.9	101371
19	b.1	Providing Laying in position Reinforced cement concrete of specified grade (M15) including the cost centering, shuttering, steel bending with binding wire (18 G annealed Steel wire), cutting, curing. Approved make cement is PPC (ACC, Ultra tech, Birla)	Reinforced cement concrete of specified grade (M15) including the cost centering, shuttering, steel bending with binding wire (18 G annealed Steel wire), cutting, curing. Approved make cement is PPC						0	
20	a	1:2:4 (1 cement : 2 coarse sand : 6 graded stone aggregate 20mm nominal size)- M15. In Shelves, counters, lintels, beams, waist slab etc.	graded stone aggregate 20mm nominal size)- M15. In Shelves, counters, lintels, beams, waist slab etc.	cuft	0.000	0.00	0		0	0
21	a.1	Brick Wall and Plaster	Brick Wall and Plaster						0	
22	a.2	Autoclaved Aerated Concrete Block	Autoclaved Aerated Concrete Block						0	
23	a.2	Providing and laying autoclaved aerated cement blocks masonry with 100 mm thick AAC blocks in super structure above plinth level in cement mortar 1:4 (1 cement : 4 coarse sand). The rate includes providing and placing in position 2 Nos 8 mm dia M.S. bars at every third course of masonry work.	Providing and laying autoclaved aerated cement blocks masonry with 100 mm thick AAC blocks in super structure above plinth level in cement mortar 1:4 (1 cement : 4 coarse sand). The rate includes providing and placing in position 2 Nos 8 mm dia M.S. bars at every third course of	Sq.Ft	0.000	0.00	0		0	0
24	a.2	Providing and laying autoclaved aerated cement blocks masonry with 150 mm thick AAC blocks in super structure above plinth level in cement mortar 1:4 (1 cement : 4 coarse sand). The rate includes providing and placing in position 2 Nos 8 mm dia M.S. bars at every third course of masonry work.	Providing and laying autoclaved aerated cement blocks masonry with 150 mm thick AAC blocks in super structure above plinth level in cement mortar 1:4 (1 cement : 4 coarse sand). The rate includes providing and placing in position 2 Nos 8 mm dia M.S. bars at every third course of	Sq.Ft	0.000	0.00	0		0	0
25	a.1	Brick Work	Brick Work						0	
26	a.1	Providing Constructing 115mm thick wall of class I Brick with conventional IS type bricks in 1:4 cement mortar inclusive of RCC tie member at every one meter height interval in 1:3:6 Cement Concrete with 2 no. of 6mm diameter mild steel reinforcement. 2 no. of hoop iron strips 25mm x 1.6mm, painted with anti-corrosive paint, properly bent and bonded at the end inclusive of shuttering, scaffolding, fitting of joints and proper curing etc. complete.	Providing Constructing 115mm thick wall of class I brick with conventional IS type bricks in 1:4 cement mortar inclusive of RCC tie member at every one meter height interval in 1:3:6 Cement Concrete with 2 no. of 6mm diameter mild steel reinforcement. 2 no. of hoop iron strips 25mm x 1.6mm, painted with anti-corrosive paint, properly bent and bonded at the end inclusive of shuttering, scaffolding, fitting of joints and proper curing etc. complete.	Sq.Ft	900.000	175.00	171500	100%	171500	171500

Approved
27/5/24

26 c	Providing and laying 9 Brick masonry work with well burnt 1st class labile moulded, good quality approved bricks in 1:6 Cement Mortar (1:6 Cement 6 Coarse Sand by volume) in true line, level and plumb for wall foundations, trenches, pedestals, columns, compound walls, steps, pillars etc. complete with necessary scaffolding, raking of joints, curing etc. complete as directed and specified upto plinth level. Rate to include soaking of bricks adequately before construction, complete as directed and specified.	cuft	7.000	350.00	2450	0%	0	0	2
27 b	Plaster								
28	Plastering the Sinores brick masonry walls with 12mm to 15mm thick. Single coat cement plaster in 1:4 (cement sand proportion) with chickenmesh jali wherever required, including scaffolding and curing complete as specified and as directed by Site Engineer.	Sq. Ft	750.000	55.00	41250	100%	41250	0	41250.00
29 a	Brickbat Coba and Water proofing providing and laying brick-bat coba system, cm 1.3 base coat, brick-bat cobs filling as per site requirement 1:4 top-finish coat, the mortar for the brick-bat koba filling shall be cm 1:4 and admixed with integral waterproofing compound	cuft	0.000	0.00	0		0	0	0
30 b	Filling mortar light weight cinder with cement salary - Providing and laying Cinder Coba cm 1.3 base coat, cinder filling as per site requirement 1:4 top-finish coat, the mortar for the cinder koba filling shall be cm 1:4 and admixed with integral waterproofing compound and mortar plasticizer	cuft	0.000	0.00	0		0	0	0
31 c	Providing of water proofing - chemical Treatment - the slab to be cleaned and apply 3 coats of chemical (FOSROC or equivalent) on the floor and waterproofing (1 layer of membrane 1.5mm to 2mm membrane	Sq. Ft	0.000	0.00	0		0	0	0
32 d	Pl one layer of 3mm APP membrane waterproofing (1 layer of membrane - Two coat layer of membrane Two coat adhesive) of approved make in toilet kitchen area or as directed by the Site Engineer minimum 2 coats with requisite adhesive compounds as per the manufacturer's specifications on floor, sub-bas slab	Sq. Ft	850.000	205.00	174250	100%	174250	0	174250.00
34	Rolling Shutter, -Awning Mild Steel work	Sq. Ft	0.000	0.00	0		0	0	0
35 a	Providing fixing Rolling Shutter including motorized mechanism to be operated with key switch of min. 20	Sq. Ft	0.000	0.00	0		0	0	0
36 b	Providing fixing manual Rolling Shutter including manual gear box of min. 20 gauge MS sheet, including floor locks, guide rail, first quality	Sq. Ft	0.000	0.00	0		0	0	0
37 c	Providing, fabricating erection of Steel work in built up section applying a priming haisting, fixing in position applying a priming coat of approved steel primer using steel etc, as required. In structure slab (ISMB, ISMC etc) or stringers, trends, landing of stair case, i/c use of structural plate wherever required - all complete	Sq. Ft	0.000	0.00	0		0	0	0
38 d	Providing and Fabricating MS louvers as per detail drawing and site engineer for Gas Bank and AC Outdoor	KG	371.380	165.00	61277.7	0%	0	0	61277.70
39 e	Providing and Fabricating Aluminium louvers as per detail drawing and site engineer for Gas Bank and AC Outdoor, diffuser 2ft x 2ft in sqft.	KG	0.000	0.00	0		0	0	0
40 f	Providing fixing Motorized Poly carbonate (minimum 3mm thickness) Rolling Shutter including motorized mechanism to be operated with key switch, of min. including floor locks, guide rail, Rate including cost of transportation, flooring and Cladding	KG	0.000	0.00	0		0	0	0
41	Flooring and Cladding	Sq. Ft	0.000	0.00	0		0	0	0
42 a	Providing and fixing in position Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4, (required mortar bed is 25mm to 50mm thick) with thick grey	Sq. Ft	0.000	0.00	0		0	0	0
43 b	Providing and fixing in position Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4, (required mortar bed is 25mm to 50mm thick) with thick grey	Sq. Ft	0.000	0.00	0		0	0	0
44 c	Providing and fixing in position Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4, (required mortar bed is 25mm to 50mm thick), with thick grey	Sq. Ft	0.000	0.00	0		0	0	0
45 d	Providing and fixing in position Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4, (required mortar bed is 25mm to 50mm thick), with thick grey	Sq. Ft	0.000	0.00	0		0	0	0

46	d.1 (cont)	Providing and fixing in position Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4. (required mortar bed is 25mm to 50mm thk) with thick grey cement	glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4. (required mortar bed is 25mm to 50mm	Sq. Ft	0.000	0.00	0	0	0.00
47		Providing and fixing in position Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4. (required mortar bed is 25mm to 50mm thk) with thick grey cement	Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4. (required mortar bed is 25mm to 50mm thk) with thick grey cement	Sq. Ft	700.000	250.00	175000	50%	R7500 175,000.00
48		Providing and fixing in position Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4. (required mortar bed is 25mm to 50mm thk) with thick grey cement slurry, with	flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4. (required mortar bed is 25mm to 50mm thk) with thick grey cement	Sq. Ft	0.000	0.00	0	0	0.00
49		Providing and fixing in position Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4. (required mortar bed is 25mm to 50mm thk) with thick grey cement slurry, with hairline joints using cement grout. The	glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4. (required mortar bed is 25mm to 50mm thk) with thick grey cement slurry,	Sq. Ft	0.000	0.00	0	0	0.00
50	h	Providing and fixing in position Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4. (required mortar bed is 25mm thk) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of tiles making smooth	Providing and fixing in position Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4. (required mortar bed is 25mm thk) with thick grey cement slurry, with hairline	Sq. Ft	0.000	0.00	0	0	0.00
51		Providing and fixing in position Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4. (required mortar bed is 25mm to 50mm thk) with thick grey	Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:4. (required mortar bed is 25mm to 50mm thk)	Rft	0.000	0.00	0	0	0.00
52		Providing and fixing in position 100 mm ht. Skirting as per detail in drawing. Over 20 mm thk bed of cement mortar 1:4 (cement fine sand) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of tiles making smooth edges wherever required for	mm ht. Skirting as per detail in drawing. Over 20 mm thk bed of cement mortar 1:4 (cement fine sand) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of tiles	Rft	0.000	0.00	0	0	0.00
53	1 ep 1	Providing and fixing in position 100 mm ht. Skirting as per detail in drawing. Over 20 mm thk bed of cement mortar 1:4 (cement fine sand) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of	Providing and fixing in position 100 mm ht. Skirting as per detail in drawing. Over 20 mm thk bed of cement mortar 1:4 (cement fine sand) with thick grey cement slurry, with	Rft	0.000	0.00	0	0	0.00
54	k	Providing and fixing in position 100 mm ht. Skirting as per detail in drawing. Over 20 mm thk bed of cement mortar 1:4 (cement fine sand) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of	Providing and fixing in position 100 mm ht. Skirting as per detail in drawing. Over 20 mm thk bed of cement mortar 1:4 (cement fine sand) with thick grey cement slurry, with	Rft	110.000	120.00	13200	0%	0 13,200.00
55		Providing and fixing in position 100 mm ht. Skirting as per detail in drawing. Over 20 mm thk bed of cement mortar 1:4 (cement fine sand) with thick grey cement slurry, with hairline joints	mm ht. Skirting as per detail in drawing. Over 20 mm thk bed of cement mortar 1:4 (cement fine sand) with thick grey cement slurry, with	Rft	0.000	0.00	0	0	0.00
56	m	Providing and fixing in position dado tile of approved make shade on any surface as per details in drawing and Over 12 mm thk bed of cement mortar 1:3 (cement fine sand) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of tiles making smooth edges wherever required. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc. Complete as specified in the drawing to the satisfaction of the Site Engineer. Ceramic wall tile (Printed) With customize line work	Providing and fixing in position dado tile of approved make shade on any surface as per details in drawing and Over 12 mm thk bed of cement mortar 1:3 (cement fine sand) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of tiles making smooth edges wherever required. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc. Complete as specified in the drawing to the satisfaction of the Site Engineer. Ceramic wall tile (Printed) With customize line work	Sq. Ft	980.000	180.00	176400	←100%	176400 176,400.00
57	n	Providing and fixing in position dado tile of approved make shade on any surface as per details in drawing and Over 12 mm thk bed of cement mortar 1:3 (cement fine sand) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of tiles making smooth edges wherever required. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc. Complete as specified in the drawing to the satisfaction of the Site Engineer.	Providing and fixing in position dado tile of approved make shade on any surface as per details in drawing and Over 12 mm thk bed of cement mortar 1:3 (cement fine sand) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of tiles making smooth edges wherever required. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc. Complete as specified in the drawing to the satisfaction of the Site Engineer.	Sq. Ft	0.000	0.00	0	0	0.00


 27/5/24

58	o	Providing and fixing in position dado tile of approved make shade on any surface as per details in drawing and Over 12 mm thk bed of cement mortar 1:3 (cement fine sand) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of tiles making smooth edges wherever required. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc. Complete as specified in the drawing to the satisfaction of the Site Engineer.	Providing and fixing in position dado tile of approved make shade on any surface as per details in drawing and Over 12 mm thk bed of cement mortar 1:3 (cement fine sand) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of tiles making smooth edges wherever required. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc. Complete as specified in the drawing to the satisfaction of the Site Engineer.	Sq. Ft.	0.000	0.00	0	0	0.00
59	p	Providing and fixing in position Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:3, required mortar bed is 25mm to 50mm thk), with thick grey cement slurry, using cement grout The job including cutting of tiles making smooth edges wherever required. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc. Complete as specified in the drawing to the satisfaction of the Site Engineer.	Providing and fixing in position Glazed Vitrified Tile flooring as per detail in drawing. It shall be fixed with cement mortar of 1:3, required mortar bed is 25mm to 50mm thk), with thick grey cement slurry, using cement grout The job including cutting of tiles making smooth edges wherever required. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc. Complete as specified in the drawing to the satisfaction of the Site Engineer.	Sq. Ft.	0.000	0.00	0	0	0.00
60	q	Providing and fixing in position dado tile of approved make shade on any surface as per details in drawing and Over 12 mm thk bed of cement mortar 1:3 (cement fine sand) with thick grey cement slurry. The job including cutting of tiles making smooth edges wherever required. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc. Complete as specified in the drawing to the satisfaction of the Site Engineer.	Providing and fixing in position dado tile of approved make shade on any surface as per details in drawing and Over 12 mm thk bed of cement mortar 1:3 (cement fine sand) with thick grey cement slurry. The job including cutting of tiles making smooth edges wherever required. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc. Complete as specified in the drawing to the satisfaction of the Site Engineer.	Sq. Ft.	0.000	0.00	0	0	0.00
61	r	Providing and fixing in position dado tile (White Tile) as per details in drawing and Over 12 mm thk bed of cement mortar 1:3 (cement fine sand) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of tiles making smooth edges wherever required. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc. Complete as specified in the drawing to the satisfaction of the Site Engineer. (Size - 200x250mm)	Providing and fixing in position dado tile (White Tile) as per details in drawing and Over 12 mm thk bed of cement mortar 1:3 (cement fine sand) with thick grey cement slurry, with hairline joints using cement grout. The job including cutting of tiles making smooth edges wherever required. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc. Complete as specified in the drawing to the satisfaction of the Site Engineer. (Size - 200x250mm)	Sq. Ft.	0.000	0.00	0	0	0.00
62	s	Providing and Fixing 19mm thick, upto 6 wide granite door frames with 6mm chamfered edges machine polished edges externally and internally. Rate to include cutting moulding polishing Transport etc. Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge. (required mortar bed is 25mm to 50mm thk)	Providing and Fixing 19mm thick, upto 6 wide granite door frames with 6mm chamfered edges machine polished edges externally and internally. Rate to include cutting moulding polishing Transport etc. Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge. (required mortar bed is 25mm to 50mm thk)	RFt	0.000	0.00	0	0	0.00
63	t	Providing Fixing 6 -8 wide band of granite of approved shade sample. It shall be fixed along the doors. (It shall be flushed with finished edge of the wall) with 1:3 cement mortar as per detailed design shall be flushed with adjoining flooring, etc. Minimum 15 mm	Providing Fixing 6 -8 wide band of granite of approved shade sample. It shall be fixed along the doors. (It shall be flushed with finished edge of the wall) with 1:3 cement mortar as per detailed design shall be flushed with adjoining flooring, etc. Minimum 15 mm	RFt	0.000	0.00	0	0	0.00

64	u	Providing and Fixing 19mm thick black granite on floor. Rate to include cutting moulding polishing Installation Transport etc. Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge.(required mortar bed is 25mm thk)	Providing and Fixing 19mm thick black granite on floor. Rate to include cutting moulding polishing Installation Transport etc. Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge.(required mortar bed is 25mm thk)	sq ft	0.000	0.00	0	0	00	
65		Providing and fixing in position Glazed Vitrified Tile Dado on Makeline POS counter as per detail in drawing. Over 12 mm thk bed of cement mortar 1:4 (cement : fine sand) with thick grey cement slurry, with hairline joints. The job including cutting of tiles making smooth edges wherever required for drain pipes. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc., complete and as directed by Engineer-in-charge. The cost should include PVC floor covering material.	Providing and fixing in position Glazed Vitrified Tile Dado on Makeline POS counter as per detail in drawing. Over 12 mm thk bed of cement mortar 1:4 (cement : fine sand) with thick grey cement slurry, with hairline joints. The job including cutting of tiles making smooth edges wherever required for drain pipes. The work shall also include cost of materials, wastages, labour, all lead and lift at all levels, loading and unloading, transportation, curing etc. and all other incidental charges etc., complete and as directed by Engineer-in-charge. The cost should include PVC floor covering material.	Sq. Ft	75.000	320.00	24000	50%	12000	24000.00
66		Interior Head	Interior Head						0	
67	a	False Ceiling	False Ceiling						0	
68	b	Gypsum Board false Ceiling Providing, fabrication and fixing in position of false ceiling (height will be decided on the spot as per site conditions) by fixing 12 mm Th. Gypsum Board sheets on frame work of GI sheet section. The main runners of 22 gauge GI sheet and cross runners of 24 gauge GI sheet must be framed to form a mesh of 2'0"x2'0" c/c. The Gypsum Board must be fixed to the GI frame and joint to be properly filled in with POP paste and paper tape to get a leveled smooth ceiling. Recessing of the Gypsum Board for light fixtures must be done along with extra frame work of GI sheet section to hold the concealed light fixtures etc. directed by the site engineer	Gypsum Board false Ceiling Providing, fabrication and fixing in position of false ceiling (height will be decided on the spot as per site conditions) by fixing 12 mm Th. Gypsum Board sheets on frame work of GI sheet section. The main runners of 22 gauge GI sheet and cross runners of 24 gauge GI sheet must be framed to form a mesh of 2'0"x2'0" c/c. The Gypsum Board must be fixed to the GI frame and joint to be properly filled in with POP paste and paper tape to get a leveled smooth ceiling. Recessing of the Gypsum Board for light fixtures must be done along with extra frame work of GI sheet section to hold the concealed light fixtures etc. directed by the site engineer	Sq. Ft	0.000	0.00	0		0	00
69	c	Providing and Fixing in position suspended type 12 mm Bison Board False Ceiling with required M.S frame (50x50 mm ,18 gauge with 1 coat of primer 2 or more coat of paint until achieved smooth finish as per drawing) work fixing arrangement of 2 x2 c/c and accessories, including groove joint filler, tapes, cut out for lights, fixing for cove pelmet box of approved size with necessary M.S. brackets supports for light fittings A.C. grills Blinds, cleaning etc. complete as per detail drawing, as specified and as directed by Site Engineer.	Providing and Fixing in position suspended type 12 mm Bison Board False Ceiling with required M.S frame (50x50 mm ,18 gauge with 1 coat of primer 2 or more coat of paint until achieved smooth finish as per drawing) work fixing arrangement of 2 x2 c/c and accessories, including groove joint filler, tapes, cut out for lights, fixing for cove pelmet box of approved size with necessary M.S. brackets supports for light fittings A.C. grills Blinds, cleaning etc. complete as per detail drawing, as specified and as directed by Site Engineer.	sqft	0.000	0.00	0		0	
70		Providing and Fixing in position suspended type 4mm thk ACP False Ceiling with required M.S frame 50x50 mm ,18 Gauge and work fixing arrangement of 2 x2 c/c and accessories, including groove joint filler, tapes, cut out for lights, fixing for cove pelmet box of approved size with necessary M.S. brackets supports for light fittings Blinds, cleaning etc. complete as per detail drawing, as specified and as directed by Site Engineer.	Providing and Fixing in position suspended type 4mm thk ACP False Ceiling with required M.S frame 50x50 mm ,18 Gauge and work fixing arrangement of 2 x2 c/c and accessories, including groove joint filler, tapes, cut out for lights, fixing for cove pelmet box of approved size with necessary M.S. brackets supports for light fittings Blinds, cleaning etc. complete as per detail drawing, as specified and as directed by Site Engineer.	sqft	0.000	0.00	0		0	00
71	a	Ceiling Elements	Ceiling Elements						0	

Aradhya
 27/5/24

72 b	Providing and Fixing in position Ceiling Suspended Metal Grid frame (1500 x 900) made out of 25x25mm m.s. hollow box pipe finished with approved shade of .5 micron powder coat . Also to have 10 mm dia m.s. rods placed on every 110 mm c c horizontally vertically, finish with approved shade of powder coat. Necessary suspension arrangement to be done with m.s. string to fix with m.s. plate anchor fasteners to the RCC slab. Complete as per detail drawing, as specified and as directed by Site Engineer.	Providing and Fixing in position Ceiling Suspended Metal Grid frame (1500 x 900) made out of 25x25mm m.s. hollow box pipe finished with approved shade of .5 micron powder coat . Also to have 10 mm dia m.s. rods placed on every 110 mm c c horizontally vertically, finish with approved shade of powder coat. Necessary suspension arrangement to be done with m.s. string to fix with m.s. plate anchor fasteners to the RCC slab. Complete as per detail drawing, as specified and as directed by Site Engineer.	Sq. Ft	0.000	0.00	0	0	0.00
73	Providing and Fixing 125mmX25mm thick wood finish with natural clear polish make suspended from ceiling. Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge.	Providing and Fixing 125mmX25mm thick wood finish with natural clear polish make suspended from ceiling. Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge.	R.ft	0.000	0.00	0	0	0.00
74 a	Wall Claddings Wall Partitions Claddings	Wall Claddings Wall Partitions Claddings					0	
75 a.(i)	Providing and fixing in position Bison Board Partition made out of 12mm thk. Bison Board both sides with necessary aluminum M.S sections (40 mm x 40 mm x 1.5 mm) framework at 600mm c c both ways in partition included bolted or welded in built up section to receive bison pallenig . The rate should include applying of two or more coats of primer , putty , complete as per standard technical specification, instructions of site engineer and as per decoration plan.	Providing and fixing in position Bison Board Partition made out of 12mm thk. Bison Board both sides with necessary aluminum M.S sections (40 mm x 40 mm x 1.5 mm) framework at 600mm c c both ways in partition included bolted or welded in built up section to receive bison pallenig . The rate should include applying of two or more coats of primer , putty , complete as per standard technical specification, instructions of site engineer and as per decoration plan.	Sq. Ft	0.000	0.00	0	0	0.00
76 a.1	Framing-Cutting of section Providing and fixing M.S frame work in built up tubular section (square hollow tubes 40 mm x 40 mm x 1.5 mm) framework at 600mm c c both ways in partition included bolted or welded in built up section to receive bison pallenig . The rate should include applying of two or more coats of primer , putty , complete as per standard technical specification, instructions of site engineer and as per decoration plan.	Framing-Cutting of section Providing and fixing M.S frame work in built up tubular section (square hollow tubes 40 mm x 40 mm x 1.5 mm) framework at 600mm c c both ways in partition included bolted or welded in built up section to receive bison pallenig . The rate should include applying of two or more coats of primer , putty , complete as per standard technical specification, instructions of site engineer and as per decoration plan.					0	
77 a.2	Providing Fixing 8 mm thk Bison board with above mentioned framing details - a.(i) (Rate will be include the cost of framing)	Providing Fixing 8 mm thk Bison board with above mentioned framing details - a.(i) (Rate will be include the cost of framing)	Sq. Ft	0.000	0.00	0	0	0.00
78 b	Providing Fixing 10 mm thk Bison board with above mention framing deatils - a.(i) (Rate will be include the cost of framing)	Providing Fixing 10 mm thk Bison board with above mention framing details - a.(i) (Rate will be include the cost of framing)	Sq. Ft	0.000	0.00	0	0	0.00
79 c	Providing and fixing in position full height ply Partition as mentioned in drawing made out of 12mm thk. Marine ply to be fixed on both sides with necessary aluminum M.S sections, framing details as mentioned above - a.(i). Items include making, cut-out for electrical swtich plates , swtich boxes and 4 ht skirting as per drawing and direction. Plyboard make should be GREEN, CENTURY OR EQUIVALENT. (Surface area of single side will be consider for billing)	Providing and fixing in position full height ply Partition as mentioned in drawing made out of 12mm thk. Marine ply to be fixed on both sides with necessary aluminum M.S sections, framing details as mentioned above - a.(i). Items include making, cut-out for electrical swtich plates , swtich boxes and 4 ht skirting as per drawing and direction .Plyboard make should be GREEN, CENTURY OR EQUIVALENT. (Surface area of single side will be consider for billing)	Sq. Ft	0.000	0.00	0	0	0.00
80 c.(i)	Providing and fixing in position Panelling made out of 12 mm thk. Bison Board of approved make on one side with necessary aluminum M.S sections, framing details as mentioned below - c.(i). (Surface area of single side will be consider for billing)	Providing and fixing in position Panelling made out of 12 mm thk. Bison Board of approved make on one side with necessary aluminum M.S sections, framing details as mentioned below - c.(i). (Surface area of single side will be consider for billing)	Sq. Ft	0.000	0.00	0	0	0.00

91	k	Providing and fixing in position 1 mm Thk. Laminate door matching with sheeham rosewood with 2 mm groove (NOVA TEAM 10091-MARINOLAM) of merinolam make. Complete as per details in drawing and as specified directed by Site Engineer. (surface area shall be measured for billing) on Columns upto 2500 mm Booth seating cladding upto 900 mm of customer area	Providing and fixing in position 1 mm Thk. Laminate door matching with sheeham rosewood with 2 mm groove (NOVA TEAM 10091-MARINOLAM) of merinolam make. Complete as per details in drawing and as specified directed by Site Engineer. (surface area shall be measured for billing) on Columns upto 2500 mm Booth seating cladding upto 900 mm of customer area	Sq. Ft	21.000	550.00	11550	50% ✓	5775	11,550.00
92	l	Providing and fixing in position 1mm Thk. Laminate (21141 Snow White) of Merinolam make. Complete as per details in drawing and as specified directed by Site Engineer. (surface area shall be measured for billing)	Providing and fixing in position 1mm Thk. Laminate (21141 Snow White) of Merinolam make. Complete as per details in drawing and as specified directed by Site Engineer. (surface area shall be measured for billing)	Sq. Ft	0.000	0.00	0		0	0.00
93	m	Providing fixing 15mmX15mm anodized Aluminium finish corner guard in approved shade powder coat matching to tile color above skirting level upto 2500 mm.	Providing fixing 15mmX15mm anodized Aluminium finish corner guard in approved shade powder coat matching to tile color above skirting level upto 2500 mm.	R. Ft	65.000	275.00	17875	70%	17875	17,875.00
94	n	Providing fixing MS Tube 25mmX25mm finish in black Powder coat (0.5 micron) for Booth area articald wall till skirting level as drawing.	Providing fixing MS Tube 25mmX25mm finish in black Powder coat (0.5 micron) for Booth area articald wall till skirting level as drawing.	R. Ft	54.000	200.00	10800	0%	0	10,800.00
95	o op1	Providing fixing 15mm wide T shape anodized Aluminium Transition strip	Providing fixing 15mm wide T shape anodized Aluminium Transition strip	R. Ft	27.000	250.00	6750	0%	0	6,750.00
96	o op2	Providing and fixing in position Brick Brick finish dado tile as per drawing . Its shall be fixed with chemical (Laticrete L335) grout -Roff Rainbow -khaki of approved make shade directly on wall. Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge.(Cost will include of Articladd directly on wall, Moratar Mixture Average thich 12-15mm , 1 4)	Providing and fixing in position Brick Brick finish dado tile as per drawing . Its shall be fixed with chemical (Laticrete L335) grout -Roff Rainbow -khaki of approved make shade directly on wall. Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge.(Cost will include of Articladd directly on wall, Moratar Mixture Average thich 12-15mm , 1 4)	Sq. Ft	0.000	0.00	0		0	0.00
97	o op3	Providing and fixing in position Brick Brick finish dado tile with grout -Roff Rainbow -khaki of approved make of approved make shade on Existing provided surface as per details in drawing and as specified directed by Site Engineer. (Cost will include of Articladd Moratar Mixture Average thich 12-15mm , 1 4)	Providing and fixing in position Brick Brick finish dado tile with grout -Roff Rainbow -khaki of approved make of approved make shade on Existing provided surface as per details in drawing and as specified directed by Site Engineer. (Cost will include of Articladd Moratar Mixture Average thich 12-15mm , 1 4)	Sq. Ft	0.000	0.00	0		0	0.00
98	o op4	Providing and fixing in Unistone Wall Cladding. Tile as per drawing . Its shall be fixed with chemical (Laticrete L335) matching grout of approved make shade on brick wall surface and as specified directed by Site Engineer.(Moratar Mixture Average thich 12-15mm , 1 4)	Providing and fixing in Unistone Wall Cladding Tile as per drawing . Its shall be fixed with chemical (Laticrete L335) matching grout of approved make shade on brick wall surface and as specified directed by Site Engineer.(Moratar Mixture Average thich 12-15mm , 1 4)	Sq. Ft	0.000	0.00	0		0	0.00
99	p op1	Providing and fixing in position Brick Brick finish dado Clay tile as per drawings . Its shall be fixed with chemical (Laticrete L335) matching grout of approved make shade on brick Wall Surface details as mentioned above on any surface as per details in drawing and as specified directed by Site Engineer.((Cost will include of tiles cladding, Mortar Mixture Thick 12-15 mm, 1 4)	Providing and fixing in position Brick Brick finish dado Clay tile as per drawings . Its shall be fixed with chemical (Laticrete L335) matching grout of approved make shade on brick Wall Surface details as mentioned above on any surface as per details in drawing and as specified directed by Site Engineer.((Cost will include of tiles cladding, Mortar Mixture Thick 12-15 mm, 1 4)	Sq. Ft	0.000	0.00	0		0	0.00
100	p op2	Providing and fixing in position Brick Brick finish dado tile coated with exterior grade sealer with 8mmX4mm . Its shall be fixed with chemical (Laticrete L335) grout- Roff Snow White on brick wall surface. Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge.(Cost will include of Articladd. Mortar Mixture Thick 12-15 mm, 1 4)	Providing and fixing in position Brick Brick finish dado tile coated with exterior grade sealer with 8mmX4mm . Its shall be fixed with chemical (Laticrete L335) grout- Roff Snow White on brick wall surface. Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge.(Cost will include of Articladd. Mortar Mixture Thick 12-15 mm, 1 4)	Sq. Ft	0.000	0.00	0		0	0.00

Approved
27/5/24

101	p op 3	Providing and fixing in position Brick Brick finish dado clay tile on brick wall surface Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge.(Cost will include Mortar Mixture Thick 12-15 mm, 1 4)	Providing and fixing in position Brick Brick finish dado clay tile on brick wall surface Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge.(Cost will include Mortar Mixture Thick 12-15 mm, 1 4)	Sq. Ft	0.000	0.00	0	0	0.00
102	q	Providing and fixing in position Brick Brick finish dado clay tile on direct brick wall surface Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge. (Cost will include Mortar Mixture Thick 12-15 mm, 1 4)	Providing and fixing in position Brick Brick finish dado clay tile on direct brick wall surface Complete as specified in the drawing to the satisfaction of the Architect Site-in-charge. (Cost will include Mortar Mixture Thick 12-15 mm, 1 4)	Sq. Ft	0.000	0.00	0	0	0.00
103	r	Providing and fixing 10 mm shera board with MS section of 25 mm * 25mm *1.5 mm(18 guage) as per drawings .	Providing and fixing 10 mm shera board with MS section of 25 mm * 25mm *1.5 mm(18 guage) as per drawings .	Sq. Ft	0.000	0.00	0	0	0.00
104		Providing and applying textured Paint on wall including 10-12 mm groove (as per drawing) of two coats of approved make shade . Filling the dents with approved Acrylic putty gypsum or approved crack filler, binder, cleaning and making the surface dust free, preparing surfaces, applying a coat of sealer or primer as per the manufacturers specifications. Applying two under coats and one finished coat of paint to achieve the required finish including scrapping the existing paint, scaffolding, cleaning etc. Complete as per detail drawing and as directed by Engineer-in-charge.	Providing and applying textured Paint on wall including 10-12 mm groove (as per drawing) of two coats of approved make shade . Filling the dents with approved Acrylic putty gypsum or approved crack filler, binder, cleaning and making the surface dust free, preparing surfaces, applying a coat of sealer or primer as per the manufacturers specifications. Applying two under coats and one finished coat of paint to achieve the required finish including scrapping the existing paint, scaffolding, cleaning etc. Complete as per detail drawing and as directed by Engineer-in-charge.	Sq. Ft	0.000	0.00	0	0	0.00
105	a	Doors Windows	Doors Windows	Sq. Ft	0.000	0.00	0	0	0.00
106	b	Providing and Fixing in position Main Entry Door as per details in drawings including outer MS sections 40 mm x 45 mm and 10 mm toughened glass to be sandwiched with pivot and hardware including S.S Brush Finish Handle 1500 mm ht (square one) with inbuilt locking Floor Spring (Ozone FS-9400 STD) provision in the floor as mentoned in the hyper linked drawing.and M.S Frame to be finish in Armada Blue Duco Paint or colour matching to Pantone shade PMS 2965 C (Cost will include all hardwares including Floor Spring ,Handle , Brush seal etc)	Providing and Fixing in position Main Entry Door as per details in drawings including outer MS sections 40 mm x 45 mm and 10 mm toughened glass to be sandwiched with pivot and hardware including S.S Brush Finish Handle 1500 mm ht (square one) with inbuilt locking Floor Spring (Ozone FS-9400 STD) provision in the floor as mentoned in the hyper linked drawing.and M.S Frame to be finish in Armada Blue Duco Paint or colour matching to Pantone shade PMS 2965 C (Cost will include all hardwares including Floor Spring ,Handle , Brush seal etc)	Sq.ft	0.000	0.00	0	0	0.00
107	c	Providing and fixing 12 mm tougthed glass door with patch fitting ,Pivot , lock and floor spring (Ozone FS-9400 STD), SS Handle H Type Ozone Equivalent 12 Inches ,Collar seal.	Providing and fixing 12 mm tougthed glass door with patch fitting ,Pivot , lock and floor spring (Ozone FS-9400 STD), SS Handle H Type Ozone Equivalent 12 Inches ,Collar seal.	Sq.ft	0.000	0.00	0	0	0.00
108	c.1	Providing and Fixing in position 35 mm Thk. wooden flush door including Vision Panel size of (300 x 500 mm) section on Teak Wood Door Frame of specified size, section well notched screwed with cutting of grooves, edges, mouldings over rough ground including necessary hardware, fittings, fixtures, conch bolt, 150 mm high, 2mm thick s.s kick Plate, Door closure ,Handle,Lock as mentioned in drg.bitumen paint to non exposed surface, lacquer melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade, etc complete as per detail drawing, as specified and as directed by engineer-in-charge.(Cost will include all the hardwares mentioned above including brush seal)	Providing and Fixing in position 35 mm Thk. wooden flush door including Vision Panel size of (300 x 500 mm) section on Teak Wood Door Frame of specified size, section well notched screwed with cutting of grooves, edges, mouldings over rough ground including necessary hardware, fittings, fixtures, conch bolt, 150 mm high, 2mm thick s.s kick Plate, Door closure ,Handle,Lock as mentioned in drg.bitumen paint to non exposed surface, lacquer melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade, etc. complete as per detail drawing, as specified and as directed by engineer-in-charge (Cost will include all the hardwares mentioned above including brush seal)	Sq.ft	0.000	0.00	0	0	0.00

109	c.2	Providing and Fixing in position 35 mm Thk. wooden flush door including Vision Panel size of (300 x 500 mm) with Granite frame including necessary hardware, fittings, pivot hinges, fixtures, conch bolt, 150 mm high, 2 mm thick s.s kick Plate, Door closure, Handle, Lock as mentioned in drg, bitumen paint to non exposed surface, Lacquer melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade, etc. complete as per detail drawing, as specified and as directed by engineer-in-charge. (Cost will include all the hardwares mentioned above and brush seal)	Providing and Fixing in position 35 mm Thk. wooden flush door including Vision Panel size of (300 x 500 mm) with Granite frame including necessary hardware, fittings, pivot hinges, fixtures, conch bolt, 150 mm high, 2 mm thick s.s kick Plate, Door closure, Handle, Lock as mentioned in drg, bitumen paint to non exposed surface, Lacquer melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade, etc. complete as per detail drawing, as specified and as directed by engineer-in-charge. (Cost will include all the hardwares mentioned above and brush seal)	Sq.ft	0.000	0.00	0	0	00
110	d	Providing and Fixing in position 35 mm Thk. Fire Rated wooden flush door including vision panel (300*500 mm) including necessary hardware, fittings, fixtures, conch bolt, 150 mm high, 2 mm thick s.s kick Plate, Door closure, Handle, Lock as mentioned in drg, bitumen paint to non exposed surface, melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade, etc. complete as per detail drawing, as specified and as directed by engineer-in-charge. (Cost will include all the hardwares mentioned above) size as per site	Providing and Fixing in position 35 mm Thk. Fire Rated wooden flush door including vision panel (300*500 mm) including necessary hardware, fittings, fixtures, conch bolt, 150 mm high, 2 mm thick s.s kick Plate, Door closure, Handle, Lock as mentioned in drg, bitumen paint to non exposed surface, melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade, etc. complete as per detail drawing, as specified and as directed by engineer-in-charge. (Cost will include all the hardwares mentioned above) size as per site	Sq.ft	0.000	0.00	0	0	00
111	d.1	Providing and Fixing in position 35 mm Thk. wooden flush door section on Teak Wood Door Frame of specified size, section well notched screwed with cutting of grooves, edges, mouldings over rough ground including necessary hardware, fittings, fixtures, conch bolt, 150 mm high s.s kick Plate (1.5 thickness), Door closure, Handle, Lock as mentioned in drg, bitumen paint to non exposed surface, matt melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade, etc. complete as per detail drawing, as specified and as directed by engineer-in-charge. (Cost will include all the hardwares mentioned above)	Providing and Fixing in position 35 mm Thk. wooden flush door section on Teak Wood Door Frame of specified size, section well notched screwed with cutting of grooves, edges, mouldings over rough ground including necessary hardware, fittings, fixtures, conch bolt, 150 mm high s.s kick Plate (1.5 thickness), Door closure, Handle, Lock as mentioned in drg, bitumen paint to non exposed surface, matt melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade, etc. complete as per detail drawing, as specified and as directed by engineer-in-charge. (Cost will include all the hardwares mentioned above)	Sq.ft	0.000	0.00	0	0	00
112	e	Providing and Fixing in position 35 mm Thk. wooden flush door including necessary hardware, fittings, fixtures, conch bolt, 150 mm high s.s kick Plate (1.5 thickness), Door closure, Handle, Lock as mentioned in drg, bitumen paint to non exposed surface, matt Lacquer melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade, etc. complete as per detail drawing, as specified and as directed by engineer-in-charge. (Cost will include all the hardwares mentioned above, including brush seal)	Providing and Fixing in position 35 mm Thk. wooden flush door including necessary hardware, fittings, fixtures, conch bolt, 150 mm high s.s kick Plate (1.5 thickness), Door closure, Handle, Lock as mentioned in drg, bitumen paint to non exposed surface, matt Lacquer melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade, etc. complete as per detail drawing, as specified and as directed by engineer-in-charge. (Cost will include all the hardwares mentioned above, including brush seal)	Sq.ft	0.000	0.00	0	0	00

113	f	Providing and Fixing Wooden Swing door in position 35 mm Thk. wooden flush door including Vision Panel size of (300 x 500) section on Teak Wood Door Frame of specified size, section well notched screwed with cutting of grooves, edges, mouldings over rough ground wooden frame cutting of grooves, edges, mouldings including necessary hardware including floor spring ,150 mm high s.s kick Plate,Handle,Lock as mentioned in drg. bitumen paint to non exposed surface, melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade etc. complete as per detail drawing, as specified and as directed by engineer-in-charge. (Cost will include all the hardwares mentioned above)	Providing and Fixing Wooden Swing door in position 35 mm Thk. wooden flush door including Vision Panel size of (300 x 500) section on Teak Wood Door Frame of specified size, section well notched screwed with cutting of grooves, edges, mouldings over rough ground wooden frame cutting of grooves, edges, mouldings including necessary hardware including floor spring ,150 mm high s.s kick Plate,Handle,Lock as mentioned in drg. bitumen paint to non exposed surface, melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade etc. complete as per detail drawing, as specified and as directed by engineer-in-charge. (Cost will include all the hardwares mentioned above)	Sq.ft	21.000	1750.00	36750	70%	25725	36,750.00
114	g	Metal fire door 2 hr fire rating with 35-40 mm thickness , vision panel (300*300) mm with push type panic bar, powder coated (Off white)As specified by project incharge(Navair Shakti Radiant)(FRG Glass- Saint Gobain Asahi Equivalent)	Metal fire door 2 hr fire rating with 35-40 mm thickness , vision panel (300*300) mm with push type panic bar, powder coated (Off white)As specified by project incharge(Navair Shakti Radiant)(FRG Glass- Saint Gobain Asahi Equivalent)	sqft	0.000	0.00	0		0	0
115	h	Providing and Fixing Wooden Swing door in position 35 mm Thk. wooden flush door including Vision Panel size of (300 x 500) including necessary hardware including floor spring ,150 mm high s.s kick Plate,Handle,Lock as mentioned in drg.bitumen paint to non exposed surface, lacquer melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade etc. complete as per detail drawing, as specified and as directed by engineer-in-charge. (Cost will include all the hardwares mentioned above)	Providing and Fixing Wooden Swing door in position 35 mm Thk. wooden flush door including Vision Panel size of (300 x 500) including necessary hardware including floor spring ,150 mm high s.s kick Plate,Handle,Lock as mentioned in drg.bitumen paint to non exposed surface, lacquer melamine polish matching to Laminate on door frames Horizontal grain Laminate on the panel from both sides of approved make shade etc. complete as per detail drawing, as specified and as directed by engineer-in-charge. (Cost will include all the hardwares mentioned above)	Sq.ft	0.000	0.00	0		0	00
116		19 MM Thk Solid Core Counter Swing Door with double side Piano S.S hinge 2 nos as mention in the detail drawing and as directed by Site Engineer .Door Front finish to be done with as Approved Tile with 38 mm corian Profile in all the sides of tile and top of Swing Door and Door inside finish with Approved Laminate. 19 MM thick patti on all the edges on all three sides (Cost will include all the hardwares mentioned above)	19 MM Thk Solid Core Counter Swing Door with double side Piano S.S hinge 2 nos as mention in the detail drawing and as directed by Site Engineer .Door Front finish to be done with as Approved Tile with 38 mm corian Profile in all the sides of tile and top of Swing Door and Door inside finish with Approved Laminate. 19 MM thick patti on all the edges on all three sides (Cost will include all the hardwares mentioned above)	Sq.ft	11.000	1750.00	19250	50%	9625	19,250.00
117	a	P.O.P Painting	P.O.P Painting						0	
118	a.1	Providing applying wall punning up to 12mm to 15mm thick layer of super fine Plaster of Paris applied on specified area over existing plastered surface on walls and columns, to be finished smooth. Surface to be prepared by hacking, sand papering and applying coat of cement slurry if required including all incidentals, making grooves, patties, sills etc. complete and as directed by engineer in charge. The finish surface should be smooth, cover up all the patch work done by electrical agencies so as to avoid unevenness and ready to take on paint. Rate including cost of transportation, loading, unloading, scaffolding, wastage, taxes etc. as directed by Engineer-in-charge.	Providing applying wall punning up to 12mm to 15mm thick layer of super fine Plaster of Paris applied on specified area over existing plastered surface on walls and columns, to be finished smooth. Surface to be prepared by hacking, sand papering and applying coat of cement slurry if required including all incidentals, making grooves, patties, sills etc. complete and as directed by engineer in charge. The finish surface should be smooth, cover up all the patch work done by electrical agencies so as to avoid unevenness and ready to take on paint. Rate including cost of transportation, loading, unloading, scaffolding, wastage, taxes etc. as directed by Engineer-in-charge.	Sq. Ft	483.000	55.00	26565	0%	0	26,565.00

Aparshn
27/5/24

119	b	Providing and applying wall punning up to 6 mm thick layer of super fine Plaster of Paris applied on specified area over existing plastered surface on walls and columns, to be finished smooth. Surface to be prepared by hacking, sand papering and applying coat of cement slurry if required including all incidentals, making grooves, patties, sills etc. complete and as directed by engineer in charge. The finish surface should be smooth, cover up all the patch work done by electrical agencies so as to avoid unevenness and ready to take on paint. Rate including cost of transportation, loading, unloading, scaffolding, wastage, taxes etc. as directed by Engineer-in-charge.	Providing and applying wall punning up to 6 mm thick layer of super fine Plaster of Paris applied on specified area over existing plastered surface on walls and columns, to be finished smooth. Surface to be prepared by hacking, sand papering and applying coat of cement slurry if required including all incidentals, making grooves, patties, sills etc. complete and as directed by engineer in charge. The finish surface should be smooth, cover up all the patch work done by electrical agencies so as to avoid unevenness and ready to take on paint. Rate including cost of transportation, loading, unloading, scaffolding, wastage, taxes etc. as directed by Engineer-in-charge.	Sq. Ft	0.000	0.00	0	0	0.00	
120	c	Providing and applying Lustre Paint on wall of approved make shade filling the dents with approved Acrylic putty gypsum or approved crack filler, binder, cleaning and making the surface dust free, preparing surfaces, applying a coat of sealer or primer as per the manufacturers specifications, applying two under coats and one finished coat of paint to achieve the required finish including scrapping the existing paint, scaffolding, cleaning etc. complete as per detail drawing, as specified and as directed by Engineer-in-charge.	Providing and applying Lustre Paint on wall of approved make shade filling the dents with approved Acrylic putty gypsum or approved crack filler, binder, cleaning and making the surface dust free, preparing surfaces, applying a coat of sealer or primer as per the manufacturers specifications, applying two under coats and one finished coat of paint to achieve the required finish including scrapping the existing paint, scaffolding, cleaning etc. complete as per detail drawing, as specified and as directed by Engineer-in-charge.	Sq. Ft	250.000	50.00	12500	0%	0	12,510.00
121	d	Providing and applying textured Paint on wall of two coats of approved make shade filling the dents with approved Acrylic putty gypsum or approved crack filler, binder, cleaning and making the surface dust free, preparing surfaces, applying a coat of sealer or primer as per the manufacturers specifications, applying two under coats and one finished coat of paint to achieve the required finish including scrapping the existing paint, scaffolding, cleaning etc. complete as per detail drawing, as specified and as directed by Engineer-in-charge.	Providing and applying textured Paint on wall of two coats of approved make shade filling the dents with approved Acrylic putty gypsum or approved crack filler, binder, cleaning and making the surface dust free, preparing surfaces, applying a coat of sealer or primer as per the manufacturers specifications, applying two under coats and one finished coat of paint to achieve the required finish including scrapping the existing paint, scaffolding, cleaning etc. complete as per detail drawing, as specified and as directed by Engineer-in-charge.	Sq. Ft	0.000	0.00	0	0	0.00	
122	e	Providing and applying Plastic Emulsion Paint on Ceiling of approved make shade filling the dents with approved Acrylic putty gypsum or approved crack filler, binder, cleaning and making the surface dust free, preparing surfaces, applying a coat of sealer or primer as per the manufacturers specifications, applying two under coats and one finished coat of paint to achieve the required finish including scrapping the existing paint, scaffolding, cleaning etc. complete as per detail drawing, as specified and as directed by Engineer-in-charge.	Providing and applying Plastic Emulsion Paint on Ceiling of approved make shade filling the dents with approved Acrylic putty gypsum or approved crack filler, binder, cleaning and making the surface dust free, preparing surfaces, applying a coat of sealer or primer as per the manufacturers specifications, applying two under coats and one finished coat of paint to achieve the required finish including scrapping the existing paint, scaffolding, cleaning etc. complete as per detail drawing, as specified and as directed by Engineer-in-charge.	Sq. Ft	670.000	40.00	26800	0%	0	26,810.00
123	f	Providing and Applying synthetic enamel paint (Armada Blue) of approved make Shade on Metal surfaces to be prepared by rubbing with coarser sand paper suitable for painting by filling all dents and crack two coat of primer. The rate includes scrapping, Filling with Putty etc complete. - Colour and pattern to be specified at site by site supervisor. Approved make - Asain paint	Providing and Applying synthetic enamel paint (Armada Blue) of approved make Shade on Metal surfaces to be prepared by rubbing with coarser sand paper suitable for painting by filling all dents and crack two coat of primer. The rate includes scrapping, Filling with Putty etc complete. - Colour and pattern to be specified at site by site supervisor. Approved make - Asain paint	sq.ft	330.040	45.00	14851.8	0%	0	14,851.80

Arceuthus
27/5/24

124	Providing and Applying Duco spray paint (Armada Blue) of approved make on Wooden Expose metal frame. Surface to be prepared by rubbing wooden surface with coarser sand paper suitable duco paint putty to be applied and finish with primer. The rate includes scrapping, Filling with Putty etc complete in spec. Approved make - Asain paint	Providing and Applying Duco spray paint (Armada Blue) of approved make on Wooden Expose metal frame. Surface to be prepared by rubbing wooden surface with coarser sand paper suitable duco paint putty to be applied and finish with primer. The rate includes scrapping, Filling with Putty etc complete in spec. Approved make - Asain paint								
125	Exterior Head	Exterior Head								
126	a	Façade Work	Exterior Head	sq.ft	0.000	0.00	0	0	0	
127	b	Providing and fixing in position GI sheet made out of 22 gauge GI-V shape round banding sheet finished with powder coating (Armada Blue) to be fixed on 100x50x60 mm Aluminium MS frameWORK with 2mm thk 50x50 mm aluminium MS angle to be painted with anti-corrosion paint on all side and powder coated aluminium rectangular tube border size 100x25x1.5 to be fixed all round the signage. Complete as per store front details and specified in drawing.	Providing and fixing in position GI sheet made out of 22 gauge GI-V shape round banding sheet finished with powder coating (Armada Blue) to be fixed on 100x50x60 mm Aluminium MS frameWORK with 2mm thk 50x50 mm aluminium MS angle to be painted with anti-corrosion paint on all side and powder coated aluminium rectangular tube border size 100x25x1.5 to be fixed all round the signage. Complete as per store front details and specified in drawing.	Sq. Ft					0	
128	c	Providing and fixing in position Shera Board Panelling made out 8 mm thk Shera board with 25mm x 50mm aluminum sections M.S framework at 600mm x 1200 mm c c with two coat of primer. Complete as per decoration plan and as specified directed by Site Engineer. (Surface area of the partition shall be measured for billing)	Providing and fixing in position Shera Board Panelling made out 8 mm thk Shera board with 25mm x 50mm aluminum sections M.S framework at 600mm x 1200 mm c c with two coat of primer. Complete as per decoration plan and as specified directed by Site Engineer. (Surface area of the partition shall be measured for billing)	Sq. Ft	75.000	550.00	41250	0%	0	41,250.00
129	d	Providing and fixing in position screen module as per details in drawing. Provision for Glass panel shutter made up from 19 mm Marine PLY frame 10 mm toughened Glass and Ply framing boxing to be made with necessary locking arrangement, Hinges, 150x 150 mm ,fastener Dorma Patch Fitting for Shutter. Complete as per detail drawing and as specified directed by Site Engineer. (Length width of the partition shall be measured for billing.)	Providing and fixing in position screen module as per details in drawing. Provision for Glass panel shutter made up from 19 mm Marine PLY frame 10 mm toughened Glass and Ply framing boxing to be made with necessary locking arrangement, Hinges, 150x 150 mm ,fastener Dorma Patch Fitting for Shutter. Complete as per detail drawing and as specified directed by Site Engineer. (Length width of the partition shall be measured for billing.)	Sq. Ft.	0.000	0.00	0	0	0	0
130	e	Providing Fixing of heavy duty cable trunking box at the floor and ceiling beam with help of necessary arrangement. Fixing of at digital display (LED TV) approved size at cable trunking box with necessary arrangement and powder coating to be done for cable trunking box in approved shade. All the necessary arrangements to be done for thincient fixing. Also all the cables to be trunked in the cable trucking box.	Providing Fixing of heavy duty cable trunking box at the floor and ceiling beam with help of necessary arrangement. Fixing of at digital display (LED TV) approved size at cable trunking box with necessary arrangement and powder coating to be done for cable trunking box in approved shade. All the necessary arrangements to be done for thincient fixing. Also all the cables to be trunked in the cable trucking box.	Nos	0.000	0.00	0	0	0	0
131	f	Providing and fixing in position fixed 10 mm Toughened glass partition with As approved Duco Painted -(ARMADA BLUE) or colour matching to Pantone shade PMS 2965 C metal frame of 40 x 45 x1.5 mm section and intermediate sections of 25 x 25 x1.5 mm from outside and 25 x 12 x1.5 mm from inside with toughened glass. Complete as per details in drawing. (Surface area of the partition shall be measured for billing.)	Providing and fixing in position fixed 10 mm Toughened glass partition with As approved Duco Painted -(ARMADA BLUE) or colour matching to Pantone shade PMS 2965 C metal frame of 40 x 45 x1.5 mm section and intermediate sections of 25 x 25 x1.5 mm from outside and 25 x 12 x1.5 mm from inside with toughened glass. Complete as per details in drawing. (Surface area of the partition shall be measured for billing.)	Sq. Ft	0.000	0.00	0	0	0	0
132	g	Providing and fixing in position fixed 10 mm Toughened glass partition with As approved powder coated on Aluminium frame of 45 x 25 mm section with glazing rubber and intermediate sections of 45 x 25 from outside and 45 x 25 from inside with toughened glass. Complete as per details in drawing. (Surface area of the partition shall be measured for billing)	Providing and fixing in position fixed 10 mm Toughened glass partition with As approved powder coated on Aluminium frame of 45 x 25 mm section with glazing rubber and intermediate sections of 45 x 25 from outside and 45 x 25 from inside with toughened glass. Complete as per details in drawing. (Surface area of the partition shall be measured for billing.)	Sq. Ft	0.000	0.00	0	0	0	0


133	h	Providing and fixing in position metal section of 25 x 25 x 1.5 mm Duco Painted in matt finish blue Paint.	Providing and fixing in position metal section of 25 x 25 x 1.5 mm Duco Painted in matt finish blue Paint.	R. Ft	0.000	0.00	0	0	0.00
134		Providing and fixing in position Trap door for rolling shutter made out of 8mm thk bison board finished with approved paint, shade to match white brick cladding, complete as per details in drawing and as specified directed by Site Engineer.	Providing and fixing in position Trap door for rolling shutter made out of 8mm thk bison board finished with approved paint, shade to match white brick cladding, complete as per details in drawing and as specified directed by Site Engineer.						
135		Wood Work	Wood Work	Sq. Ft	0.000	0.00	0	0	0.00
136	a	Furniture WOOD Work	Furniture WOOD Work						
137	a.1	Providing and fixing in position Order counter Counter top finished in 6mm thick Acrylic Solid Surface LG Hausys-HI-MACS G109 Beige Island over 19 mm thick WPC Marine Ply. 150mm height Drawers (2 nos) to be provided below each POS. Internal area to be finish with 1 mm thick approved laminate with necessary hardwares (Lock, Telescopic channel etc). MS powder coated framework (40x40x1.5mm) as per detail drawing to be provided with necessary arrangement and Ledge having LED cove strip as per detail drawing Complete in all respect. Cost to include all materials, DMB Framing, labours and necessary leads lift etc. -Counter Height-3 6	Providing and fixing in position Order counter Counter top finished in 6mm thick Acrylic Solid Surface LG Hausys-HI-MACS G109 Beige Island over 19 mm thick WPC Marine Ply. 150mm height Drawers (2 nos) to be provided below each POS. Internal area to be finish with 1 mm thick approved laminate with necessary hardwares (Lock, Telescopic channel etc). MS powder coated framework (40x40x1.5mm) as per detail drawing to be provided with necessary arrangement and Ledge having LED cove strip as per detail drawing Complete in all respect. Cost to include all materials, DMB Framing, labours and necessary leads lift etc. Counter Height-3 6	RFT	7.000	14000.00	98000	78400	98,010.00
138	b	Providing and fixing in position Order counter Counter top finished in 6mm thick Acrylic Solid Surface LG Hausys-HI-MACS G109 Beige Island over 19 mm thick WPC Marine Ply. 150mm height Drawers (2 nos) to be provided below each POS. Internal area to be finish with 1 mm thick approved laminate with necessary hardwares (Lock, Telescopic channel etc). MS powder coated framework (40 x 40 x 1.5 mm) with 10 mm toughened glass and having provision of sliding glass opening with necessary fittings and channels as per detail drawing and Ledge having LED cove strip as per detail drawing Complete in all respect. Cost to include all materials, DMB Framing, labours and necessary leads lift etc. Counter Height-3 6	Providing and fixing in position Order counter Counter top finished in 6mm thick Acrylic Solid Surface LG Hausys-HI-MACS G109 Beige Island over 19 mm thick WPC Marine Ply. 150mm height Drawers (2 nos) to be provided below each POS. Internal area to be finish with 1 mm thick approved laminate with necessary hardwares (Lock, Telescopic channel etc). MS powder coated framework (40 x 40 x 1.5 mm) with 10 mm toughened glass and having provision of sliding glass opening with necessary fittings and channels as per detail drawing and Ledge having LED cove strip as per detail drawing Complete in all respect. Cost to include all materials, DMB Framing, labours and necessary leads lift etc. Counter Height-3 6	RFT	0.000	0.00	0	0	0.00
139	c	Providing and fixing in position Makeline Counter top finished in 6mm thick Acrylic Solid Surface LG Hausys-HI-MACS G109 Beige Island over 19 mm thick Marine Ply WPC and Ledge having LED cove strip as per detail drawing Complete in all respect. Duco Paint M.S framework with 10 mm toughened Glass as per detail drawing above counter Cost to include all materials, labours and necessary leads lift etc.	Providing and fixing in position Makeline Counter top finished in 6mm thick Acrylic Solid Surface LG Hausys-HI-MACS G109 Beige Island over 19 mm thick Marine Ply WPC and Ledge having LED cove strip as per detail drawing Complete in all respect. Duco Paint M.S framework with 10 mm toughened Glass as per detail drawing above counter Cost to include all materials, labours and necessary leads lift etc.	RFT	14.000	14000.00	196000	156800	196,010.00
140	d	Providing and fixing in position MOP storage made of 18mm thk. Marine ply in appd. Laminate from outside and white laminate inside with necessary support framework. Cost to include shelves in 18 mm thk. marine ply finished in white laminate with all hardware, fasteners, and rubber PVC leveller etc. complete in all respect as per detailed drawing and size to be considered in Width x Height for Billing Depth 500 mm	Providing and fixing in position MOP storage made of 18mm thk. Marine ply in appd. Laminate from outside and white laminate inside with necessary support framework. Cost to include shelves in 18 mm thk. marine ply finished in white laminate with all hardware, fasteners, and rubber PVC leveller etc. complete in all respect as per detailed drawing and size to be considered in Width x Height for Billing Depth 500 mm	Sq. ft	0.000	0.00	0	0	0.00
141	e	Providing and Fixing in position softboard as specified size. complete in all respect as per detailed drawing. Panel Size 1200 x 900	Providing and Fixing in position softboard as specified size. complete in all respect as per detailed drawing. Panel Size 1200 x 900	Nos.	1.000	2500.00	2500	0	2,510.00

70%

70%

Aradhya
27/8/24

142	f	Providing and placing foldable staff table in position 40mm thk table top made out of 2 nos 19mm thk marine ply finished with 1mm thk laminate LAM01 on both side and edges to be finished with PVC edge bending to be supported on L bracket with Table bracket (HAFFLE) complete in all respect as per detailed drawing. Size- 4 x 1.6 , width can be adjusted as per site. Fixing of table to be kept 3 from thr floor.	Providing and placing foldable staff table in position 40mm thk table top made out of 2 nos 19mm thk marine ply finished with 1mm thk laminate LAM01 on both side and edges to be finished with PVC edge bending to be supported on L bracket with Table bracket (HAFFLE) complete in all respect as per detailed drawing. Size- 4 x 1.6 , width can be adjusted as per site. Fixing of table to be kept 3 from thr floor.	Sq.ft	5.800	1000.00	5800	50%	2900	5,800.00
143	g	Providing and fixing in position M. S. Railing made out of 25 x 25 x 1.5 MS hollow section for vertical sections and 12 x 12 x 1.5 mm midrails finished in matt duco paint as per approved shade and wooden section Hardwood oak 50 x 25 mm (With Malamine Matt Polished) Handrail to be fixed on 6 mm x 50 mm M.S flat and End to End Main Balusters will be in size of 50 x 50 mm Cost to include all hardware and fasteners etc. complete in all respect as per detailed drawing.	Providing and fixing in position M. S. Railing made out of 25 x 25 x 1.5 MS hollow section for vertical sections and 12 x 12 x 1.5 mm midrails finished in matt duco paint as per approved shade and wooden section Hardwood oak 50 x 25 mm (With Malamine Matt Polished) Handrail to be fixed on 6 mm x 50 mm M.S flat and End to End Main Balusters will be in size of 50 x 50 mm Cost to include all hardware and fasteners etc. complete in all respect as per detailed drawing.	R. Ft	0.000	0.00	0		0	0.00
144	h	Providing and fixing in position S. S. Railing made out of ss grade 304 hollow section for vertical sections and midrails and S.S Hollow handrail . Cost to include all hardware and fasteners etc. complete in all respect as per detailed drawing.	Providing and fixing in position S. S. Railing made out of ss grade 304 hollow section for vertical sections and midrails and S.S Hollow handrail . Cost to include all hardware and fasteners etc. complete in all respect as per detailed drawing.	R. Ft	0.000	0.00	0		0	0.00
145	i	Removing and re-fixing in position existig S. S. Railing M.S Railing with glass panels for installation of finishing material of tread riser. Cost to include all hardware, fasteners, and rubber PVC leveller etc. complete in all respect as per detailed drawing.	Removing and re-fixing in position existig S. S. Railing M.S Railing with glass panels for installation of finishing material of tread riser. Cost to include all hardware, fasteners, and rubber PVC leveller etc. complete in all respect as per detailed drawing.	LS	0.000	0.00	0		0	0.00
146	j	Providing and placing in position 6mm thk extra clear mirror of size 450mm x 1200 mm with 12mm thk marine ply at back to be fixed over ss stud on wall. Cost to include all hardware, fasteners, and rubber PVC leveller etc. complete in all respect as per detailed drawing.	Providing and placing in position 6mm thk extra clear mirror of size 450mm x 1200 mm with 12mm thk marine ply at back to be fixed over ss stud on wall. Cost to include all hardware, fasteners, and rubber PVC leveller etc. complete in all respect as per detailed drawing.	Nos.	0.000	0.00	0		0	0.00
147	k	Providing and fixing in place Hood Graphic Panel made out of approved shade powder coated sheet metal Complete as per details in drawing Reference Drawing No. 960	Providing and fixing in place Hood Graphic Panel made out of approved shade powder coated sheet metal Complete as per details in drawing Reference Drawing No. 960	sq ft	0.000	0.00	0		0	0.00
148	l	Providing and fixing ceiling mounted ,Metal fabricated Computer Holder for Thin clients above Dough Tray Router. Complete in all respect as per detailed drawing.	Providing and fixing ceiling mounted ,Metal fabricated Computer Holder for Thin clients above Dough Tray Router. Complete in all respect as per detailed drawing.	Nos.	1.000	5500.00	5500	0%	0	5,500.00
149	m	Providing and fixing Wall mounted ,Metal fabricated Computer Holder for Thin clients above Dough Tray Router. Complete in all respect as per detailed drawing.	Providing and fixing Wall mounted ,Metal fabricated Computer Holder for Thin clients above Dough Tray Router. Complete in all respect as per detailed drawing.	Nos.	1.000	5500.00	5500	0%	0	5,500.00
150	n	Providing fixing in position Corian foldable ledge to be made up of 6mm corian with necessary angle bracket support required to fix on m.s frame. It shall be fixed with Chemical Adhesive . The job including cutting of corian making smooth edges wherever required . The work shall also include cost of materials, wastages,bracket, labour, all lead and lift at all levels, loading and unloading, transportation, etc. and all other incidental charges etc. complete and as directed by Engineer-in-charge. Measurement to be calculated basis on Actual area in running feet.	Providing fixing in position Corian foldable ledge to be made up of 6mm corian with necessary angle bracket support required to fix on m.s frame. It shall be fixed with Chemical Adhesive . The job including cutting of corian making smooth edges wherever required . The work shall also include cost of materials, wastages,bracket, labour, all lead and lift at all levels, loading and unloading, transportation, etc. and all other incidental charges etc. complete and as directed by Engineer-in-charge. Measurement to be calculated basis on Actual area in running feet.	ft	0.000	0.00	0		0	0.00


 27/8/24