E.D NUMERAL WALES STREM Image: comparison of the state of the sta	Е			Plumbing				
a Providing & fixing on rule / colling / fixing . (concern), carpo, cet show, reduce, markelende etc. necessary filings. (Suprem: / Three Actual or a approved.) a 1. Disma contrain loss of main a sequence of fittings is concerned. PMT 0 a 2.1 Disma contrain loss of main a sequence of the sequenc	Ľ	E.1.0						
a pips of dameter a meninore below with filing is connector, damp, exe, et drow, relation, sector, filing, Seguration, Piper, Aural or approx.1. Mathematical and the sector of the sec		1.1.0						
Image: Second State			9					
Image: second			u					
Image: space			o 1		PMT	0	<u> </u>	<u> </u>
Image: Section 1 BATT 42 Image: Section 2 BATT 1 Image: Section 2 BATT 1 Image: Section 2 BATT 6 Image: Section 2 Batter 2 Batter 2 Image: Section 2					-	-		
Image: Second								-
b Providing & fixing of BI Mark CPVC haft upsee of billowing duppes as mentioned below Males sugmentation of the automation automatio automation automate automation automation automation au					-			-
B IMALe - segme/proceedual or a genome. No.			a.5	40mm nominal bore	RMT	6		-
Image: Second			h	Providing & fixing of ISI Mark CPVC ball valves of followig dia pipes as mentioned below				
Image: space of the s						0	L	. <u> </u>
Image: Product of the second						-	<u> </u>	-
Image: Solution of the second seco						-	<u> </u>	
Image: state of the s							<u> </u>	-
c Providing & fixing on walls / ceiling / floors, C class G I C class pips of flameter as mentioned lector with screwed sockes, joints & necessary. Gaprene / Prime/Attal or a suproved.) RMT 0 c.1 25MM nominal bore RMT 0 c.2 90 MM nominal bore RMT 0 d c.2. 90 MM nominal bore RMT 0 d cata valve with wheel tested to non shock cold working pressure upto 10 kg a (crtics/top Valve) conforming to 15 778 class 11 Non 4 d d.1 25m class 10 Non 4 d.2 25m class 10 Non 4 c.3 25m class 10 Non 4 c.4 40 mm class 10 Non 4 c.5 50 mm class 10 Non 0 e 61 mm class 10 Non 0 f.1 25 mm class 10 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>-</td>								-
Image: Constraint local set of the second sectors is joints & necessary. (Supreme / Prince: Astral or as approved.) Image: Constraint local set of the second sectors is joints & necessary. (Supreme / Prince: Astral or as approved.) Image: Constraint local set of the second			0.5		1105.	0		
Image: clip and clip a			с					
Image: second								
a Providing, Fixing, Lesting and commissioning of SH mated Gan Metal Screweb priol 0 kg/ag cmtStop Valvo d Gate valve with wheel tested to non shock coll working pressure poil 0 kg/ag cmtStop Valvo d d.1 20mm class 1.0 d.2 25mm class 1.0 Nos e.3 32am class 1.0 Nos e.4 40mm class 1.0 Nos e.4 40mm class 1.0 Nos e.5 50 mm class 1.0 Nos e 64 40mm class 1.0 Nos e 80 mm class 1.0 Nos 0 e Providing aff sing breas hall balve with CP copper connecting pipe 375 mm long and maix sudar and CP brass flange complete including certain guide walls Nos 0 f.1 12 mm normal bore Nos 0 10 f.2 32 mm normal bore Nos 0 10 f.2 32 mm normal bore Nos 0 10 f.1 24 mm normal bore Nos 0 10 10 f.2 32 mm normal bore Nos 0 10 10 a A0 mm norinal bore Nos 0 10 </td <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>───</td> <td></td>							───	
d Gate valve with wheel tested to non shock cold working pressure upto 10 kg vg networks of the valve of conforming to 15 778 class i. including jointing, supporting etc complete and as indicated inclusions. Joint Conformation 2019 (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (199		-	c.2			0	┣───	
a conforming to ST 78 chas 1 including jointing, supporting etc complete and as directed Quantoss/Lobio accuivalent) Nos 4 i d.1 20mm chas 1.0 Nos 4 inclusion i d.2 25mm chas 1.0 Nos 4 inclusion i c.3 32mm chas 1.0 Nos 0 inclusion i c.4 40mm chas 1.0 Nos 0 inclusion Nos 0 i f.1 10mm nominal bore Nos 0 inclusion 0 inclusion								
Image: constraint of the second se			d					
Image: state of the state o				directed.(Danfoss/Jayhiwa/Zoloto or equivalent)			\vdash	<u> </u>
i c.3 32mm class 1.0 Nos 3 i c.4 40mm class 1.0 Nos 0 i c.5 50 mm class 1.0 Nos 0 i c.5 50 mm class 1.0 Nos 0 i c.5 50 mm class 1.0 Nos 0 i e and nots waker and CP brass fange complete including cutting and making good the walls where required Nos 0 i f.1 25 mm nominal bore Nos 0 1 i f.2 32 mm nominal bore Nos 0 1 i f.3 40 mm nominal bore Nos 0 1 i f.3 40 mm nominal bore Nos 0 1 i f.3 40 mm nominal bore Nos 0 1 i f.3 40 mm nominal bore Nos 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					-		\square	-
i c.4 40mm class 1.0 Nos 0 i c.5 50 mm class 1.0 Nos 0 i c.5 50 mm class 1.0 Nos 0 i e Broviding & Fixing 15 mm C.P brass angle valve with C.P copper connecting pipe 375 mm long and nuts waker and C.P brass hange complete including cutting and making good the wails where required where required Nos 0 i f Providing and fixing brass ball balve with SS 304 stem and ball,teflon seat complete. Image: Complete including cutting and making good the wails where required Nos 0 i f.1 25 mm nominal bore Nos 0 Image: Complete including including cutting and making good the wails where required Nos 0 i f.2 32 mm nominal bore Nos 0 i f.3 40 mm morinal bore Nos 0 i f.3 40 mm nominal bore Nos 0 i a Moring is 15.7352, and 15.4985 to withstand continous internal hydroulic pressure of 4 kg/cm2 including necessary fittures and fittings, such as bachs, tees, Clance and joining with rubber rings and lubricants, on wall by means of clips or in ground including necessary excavation, laying refilling, track and there and and there and an an an and an and an and an an an and an an an and an an an an and an and an an an and an							L	
c.5 50 mm class 1.0 Nos 0 e Providing & Frising 15 mm C.P brass angle value with C.P copper connecting pipe 375 mm long and nuts washer and C.P brass flage complete, including cutting and making good the walls where required where required in the washer and C.P brass flage complete, including cutting and making good the walls washer and C.P brass flage complete, including cutting and making good the walls Nos 0 f.1 25 mm nominal bore Nos 0 1 f.3 40 mm nominal bore Nos 0 1 f.3 40 mm nominal bore Nos 0 1 e2.0 INTERNAL DRAINAGE SYSTEM Nos 0 a Providing and fixing UPCC SOIL / VENT / WASTE SWR pipe of required diameter conforming to 1.S13592, and 1.S4985 to withstand continous internal hydrouic pressure of 4 kg/cm2 including necessary fixtures and hydrouic pressure of 4 kg/cm2 including necessary fixtures and hydrouic pressure of 4 kg/cm2 including necessary fixtures and hydrouic pressure of 4 kg/cm2 including necessary fixtures and hydrouic pressure of 4 kg/cm2 including necessary fixtures and the pressure of 4 kg/cm2 including necessary fixtures and the first and and the pressure of 4 kg/cm2 including necessary fixtures and first and and the m 0 a.1 32 mm dia m 0 14 a.2 40 mm dia m 0 14 a.3 50 mm dia.					-		 	
No. Providing & Fixing 15 mm CP brass angle value with CP copper connecting pipe 375 mm long where required where required including cutting and making good the walls Nos 0 f Providing and fixing brass hall balve with SS 304 stem and ball.teflon seat complete. Nos 0 f.1 25 mm nominal bore Nos 0 f.2 32 mm nominal bore Nos 0 f.3 40 mm nominal bore Nos 0 F.2.0 INTERNAL DRAINAGE SYSTEM Nos 0 a Providing and fixing UPVC SOIL / VENT / WASTE SWR pipe of required diameter conforming to 151392, and 154985 to withstand continuous internal hydrodic pressure of 4 kg/cm2 including necessary fixtures and fittings, such as bends (see; Clean ort plugs for the downtaces near bench), single junctions, double junctions and joining with rubber rings and hubricants, on wall by means of clips or in ground including necessary excavation, laying refilling, trench testing etc. complete. (Prior approval of sample and brand by Ex.Engineer is necessary before use.) (Supremice Vence/Astral or as approved.) m 0 a.1 32 mm dia m 0 m 0 a.2 40 mm dia. m 0 m 0 a.3 50 mm dia. m 0 0 m 0							 	-
e and mut swaher and C.P brass flange complete including cutting and making good the walls where required the providing and fixing brass ball balve with SS 304 stem and ball.teflon seat complete. Nos 0 f.1 25 mm nominal bore Nos 0 f.2 32 mm nominal bore Nos 0 f.3 40 mm nominal bore Nos 0 F.2.0 INTERNAL DRAINAGE SYSTEM Nos 0 a Providing and fixing UPVC SOIL / VENT / WASTE SWR pipe of required diameter conforming to 1513592, and 154985 to withstand cominous interal hydrolic pressure of 4 kg/cm2 including necessary fixtures and fittings, such as bends, tees.Clean on taples for the downtakes near bends). single junctions, double junctions and joining with nubber rings and lubricants. on wall by means of clips or in ground including necessary exacution, laying refilling, terench tessing etc. complete. (Prin approval of sample and brand by Ex.Engineer is necessary before use.) (Supreme / Prince/Astral or as approved.) m 0 a.1 32 mm dia m 0 m 0 a.3 50 mm dia. m 0 0 a.4. 65 mm dia. m 0 0 a.5 75 mm dia. m 0 0 a.6 110 mm dia. m 0 0 a.7 H50 mm dia. m 0 0 a.7 150 mm dia. m 0 <t< td=""><td></td><td></td><td>c.5</td><td></td><td>Nos</td><td>0</td><td></td><td>-</td></t<>			c.5		Nos	0		-
intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation intermediation inttermediatin intermediatin <td< td=""><td></td><td></td><td>0</td><td><i>e e i i i i i i</i></td><td>Nos</td><td>0</td><td></td><td>_</td></td<>			0	<i>e e i i i i i i</i>	Nos	0		_
f Providing and fixing brass ball balve with SS 304 stem and ball,terflon seat complete. Image: complete			Ľ		1403	Ŭ		-
f.2 32 mm nominal bore Nos 0 E.2.0 INTERNAL DRAINAGE SYSTEM Nos 0 a INTERNAL DRAINAGE SYSTEM Nos 0 a INTERNAL DRAINAGE SYSTEM International providing and fixing UPVC SOIL / VENT / WASTE SWR pipe of required diameter conforming to 1.5.13592, and 1.5.4988 to withstand continous internal hydroulic pressure of 4 kg/cm2 including necessary fixings and labricants, on wall by means of clips or in grounds including necessary fixings and labricants, on wall by means of clips or in ground including necessary fixing refuling, trench testing etc. complete. (Prior approval of sample and brand by Ex.Engineer is necessary before us.) (Supreme / Prince/Astral or as approved.) m 0 a.1 32 mm dia m 14 m 0 a.2 40 mm dia m 14 m 0 0 a.3 30 mm dia m 0 0 0 0 a.4 65mm dia m 0 0 0 0 0 a.5 75 mm dia. m 20 0 0 0 0 0 b Chilly trap of required sizes, including joining etc. complet and as directed. (GMGR/Chilly or equivalent) m 0 0 c.4 GSmm d			f					
F.3 40 mm nominal bore Nos 0 E.0 INTERNAL DRAINAGE SYSTEM Nos 0 a Providing and fixing UPVC SOIL / VENT / WASTE SWR pipe of required diameter conforming to 1.5.13592, and 1.54983 to withstand continous internal hydroulic pressure of 4 kg/cm2 including necessary fixtures and fittings, such as bench, teesc, Clean out plugs (for the downtakes near bench). single junctions, double junctions and joining with rubber rings and lubricants, on wall by means of clips or in ground including necessary exeavation, laying refilling, trench testing etc. complete. (Prior approval of sample and brand by Ex.Engineer is necessary before use.) (Supreme / Prince/Astral or as approved.) m 0 a.1 32 mm dia m 0 m 14 a.3 50 mm dia. m 0 m 0 a.4. 65mm dia. m 20 10 14 a.5 75 mm dia. m 20 10 10 14 10 a.6 110 mm dia. m 20 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 <			f.1	25 mm nominal bore	Nos	0		-
E2.0 INTERNAL DRAINAGE SYSTEM a Providing and fixing UPVC SOIL / VENT / WASTE SWR pipe of required diameter conforming to 1.S.13592, and 1.S.4985 to withstand continous internal hydroulic pressure of 4 kg/cm2 including necessary fixtures and fittings, such as bends, tesc.Clean out plugs (for the downtakes near bends), single junctions, double junctions and joining with rubber rings and lubricratics, no wall by means of clips or in ground including necessary execuation, haying refulling, trench testing etc. complete. (Prior approval of sample and brand by Ex.Engineer is necessary before use.) (Supreme / Prince/Astral or as approved.) m 0 a.1 32 mm dia m 14 a.2 40 mm dia m 0 a.4 65mm dia m 0 a.5 75 mm dia. m 20 a.6 110 mm dia. m 20 a.7 150 mm dia. m 0 providing laying, testing & commissioning of approved Multi floor trap / Nahani trap with Chilly trap of required sizes, including jointing etc. complete and as directed. (GMGR/Chilly or equivalent) Nos. 1 b STIC RO Water booster pump upto 1 HP Auto Cut Type , mounting with rubber pad & mt bolt (Make Compton Grundfoss, Danfoss, Kirloskar or equivalent) Nos. 1 c e STIC RO Water booster pump upto 1 HP Auto Cut Type , mounting with rubber pad & mt bolt (Make Compton Grundfoss, D			f.2	32 mm nominal bore	Nos	0		-
a Providing and fixing UPVC SOL / VENT / WASTE SWR pipe of required diameter conforming to 1.S-13592, and 1.S. 4985 to withstand continous internal hydroulic pressure of 4 kg/cm2 including necessary excess(Clean out plugs (for the downtakes near bends). single junctions, double junctions and joining with rubber rings and lubricants, on wall by means of clips or in ground including necessary excavation, laying refilling, trench testing etc. complete. (Prior approved) of sumple and brand by Ex.Engineer is necessary before use.) (Supreme / Prince/Astral or as approved.) m 0 a.1 32 mm dia m 0 m 0 a.2 40 mm dia m 0 m 0 a.3 50 mm dia. m 0 m 0 a.4 65mm dia. m 0 m 0 a.6 110 mm dia. m 20 m 0 b Providing laying, testing & commissioning of approved Multi floor trap / Nahani trap with Chilly trap of required sizes, including jointing etc. complete and as directed. (GMGR/Chilly or equivalent) Nos. 1 c SITC RO Water booster pump upto 1 HP Auto Cut Type, mounting with rubber pad & nut bolt (Make Crompton Grundfoss, Danfoss, Kirlokar or equivalent) Nos 1 d GITC RO Water booster pump 0.5 HP Auto Cut Type, mounting with rubber pad & nut bolt (Make Crompton Grundfoss, Danfoss, Kirlokar or equivalent) 0<			f.3	40 mm nominal bore	Nos	0		-
a conforming to 1.513592, and 1.54985 to withstand continous internal hydroulic pressure of 4 kg/cm2 including necessary fixtures and fittings, such as bends, tees,Clean out plugs (for the downtakes near bends). single junctions and joining with rubber rings and lubricants, on wall by means of clips or in ground including necessary excavation, laying refilling, trench testing etc. complete. (Prior approval of sample and brand by Ex.Engineer is necessary before us.) (Supreme / Prince/Astral or a sapproved.) m 0 a.1 32 mm dia m 0 14 a.2 40 mm dia m 0 14 a.3 50 mm dia. m 0 0 a.4 65tmm dia m 0 0 a.5 75 mm dia. m 20 0 a.6 110 mm dia. m 0 0 b Chilly trap of required sizes, including jointing etc. complete and as directed. (GMGR/Chilly or equivalent) Nos. 5 b SITC RO Water booster pump upto 1 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grund/os, Danfos, Kirloskar or equivalent) Nos. 1 clil d d SITC RO Water booster pump upto 1 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grund/os, Danfos, Kirloskar or equivalent) 0 0 clil d G		E.2.0		INTERNAL DRAINAGE SYSTEM				
a kg/cm2 including necessary fixtures and fittings, such as bends, tees,Clean out plugs (for the downtakes near bends). single junctions, double junctions and joining with rubber rings and lubricants, on wall by means of clips or in ground including necessary excessary supervised. Image: supervised of the downtakes near bends). Single junctions, double junctions, and joining with rubber rings and lubricants, on wall by means of clips or in ground including necessary excessary before use.) (Supreme / Prince/Astral or as approved.) Image: supervised of the downtakes near bends). Image: supervised of the downtakes near bends). Image: supervised of the downtakes near bends). Image: supervised of the downtakes near bends). Image: supervised of the downtakes near bends). Image: supervised of the downtakes near bends). Image: supervised of the downtakes near bends). Image: supervised of the downtakes near bends). Image: supervised of the downtakes near bends). Image: supervised of the downtakes near bends. Image: supervised of the downtakes near bends of the downtakes near bends. Image: supervised of the downtakes neare bends. Image: supervised				Providing and fixing UPVC SOIL / VENT / WASTE SWR pipe of required diameter				
a downtakes near bends). single junctions, double junctions and joining with rubber rings and lubricants, on wall by means of clips or in ground including necessary exeavation, laying refilling, trench testing etc. comproved of sample and brand by Ex.Engineer is necessary before use.) (Supreme / Prince/Astral or as approved.) m 0 a.1 32 mm dia m 0 a.2 40 mm dia m 0 a.3 50 mm dia. m 0 a.4 65mm dia m 0 a.5 75 mm dia. m 0 a.6 110 mm dia. m 20 a.7 150 mm dia. m 0 b Providing Jaying, testing & commissioning of approved Multi floor trap / Nahani trap with Chilly trap of required sizes, including jointing etc. complete and as directed. (GMGR/Chilly or equivalent) Nos. 5 b SITC RO Water booster pump upto 1 HP Auto Cut Type, mounting with rubber pad & nut bolt (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) Nos. 1 d A Sitter RO Water booster pump of 1 PP Auto Cut Type, mounting with rubber pad & nut bolt (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) Nos. 1 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects								
Image: state of the state of								
Image: string			a					
a.1 32 mm dia m 0 a.2 40 mm dia m 14 a.3 50 mm dia. m 0 a.4 65mm dia m 0 a.5 75 mm dia. m 20 a.6 110 mm dia. m 20 a.7 150 mm dia. m 0 b Chily trap of required sizes, including jointing etc. complete and as directed. (GMGR/Chilly or equivalent) Nos. 5 b Chily trap of required sizes, including jointing etc. complete and as directed. (GMGR/Chilly or equivalent) Nos. 1 clip e SITC RO Water booster pump upto 1 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) Nos. 1 f Guade Compton Grundfoss, Danfoss, Kirloskar or equivalent) Nos. 1 f Guadit fixing of PVC water vertical type storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessiories.(Sintex or equivalent make of Capacity - 200-2050 ltrs) Nos 1 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessiories.(,			
Image: constraint of the second sec				before use.) (Supreme / Prince/Astral or as approved.)				
a.3 50 mm dia. m 0 a.4 65mm dia m 0 a.5 75 mm dia. m 20 a.6 110 mm dia. m 20 a.7 150 mm dia. m 20 a.7 150 mm dia. m 0 b Providing laying, testing & commissioning of approved Multi floor trap / Nahani trap with Chilly trap of required sizes, including jointing etc. complete and as directed. (GMGR/Chilly or equivalent) m 0 b SITC RO Water booster pump upto 1 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) Nos. 1 d SITC RO Water booster pump 0.5 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) 0 f Providing and fixing of PVC water vertical type storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessiories. (Sintex or equivalent make of Capacity - 200-250 Itrs) Nos 1 g Providing and fixing of PVC water storage tanks of the approved quality, including make point and fixing of PVC water storage tanks of the approved quality including make point and fixing of PVC water storage tanks of the approved quality including making solid work complete in all respects with gate valve and necessary make point			a.1	32 mm dia	m	0		-
a.465mm diam0a.575 mm dia.m20a.6110 mm dia.m20a.7150 mm dia.m0bProviding, laying, testing & commissioning of approved Multi floor trap / Nahani trap with Chilly trap of required sizes, including jointing etc. complete and as directed. (GMGR/Chilly or equivalent)Nos.5ceSITC RO Water booster pump upto 1 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss,Danfoss, Kirloskar or equivalent)Nos.1dSITC RO Water booster pump 0.5 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss,Danfoss, Kirloskar or equivalent)Nos.1fproviding and fixing of PVC water vertical type storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessiories.(Sintex or equivalent make of Capacity - 200-250 ltrs)Nos1gProviding and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent make)Ltr0E.3.0EXTERNAL SEWERAGEImage: Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fineImage: Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine				40 mm dia	m	14		-
Image: space of the system o			a.3	50 mm dia.	m	0		-
a.6110 mm dia.m20a.7150 mm dia.m0bProviding ,laying, testing & commissioning of approved Multi floor trap / Nahani trap with Chilly trap of required sizes, including jointing etc. complete and as directed. (GMGR/Chilly or equivalent)Nos.5eSITC RO Water booster pump upto 1 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss,Danfoss, Kirloskar or equivalent)Nos.1ddSITC RO Water booster pump 0.5 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss,Danfoss, Kirloskar or equivalent)Nos.1fProviding and fixing of PVC water vertical type storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessiories .(Sintex or equivalent make of Capacity - 200-250 Itrs)Nos1gProviding and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories.(Sintex or equivalent make of Capacity - 200-250 Itrs)Nos1gEx.3.0EXTERNAL SEWERAGEItr0			a.4		m			-
a.7 150 mm dia. m 0 b Providing Jaying, testing & commissioning of approved Multi floor trap / Nahani trap with Chilly trap of required sizes, including jointing etc. complete and as directed. (GMGR/Chilly or equivalent) m 0 e SITC RO Water booster pump upto 1 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss,Danfoss, Kirloskar or equivalent) Nos. 1 d SITC RO Water booster pump 0.5 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss,Danfoss, Kirloskar or equivalent) 0 f Providing and fixing of PVC water vertical type storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessiories .(Sintex or equivalent make of Capacity - 200-250 Itrs) Nos 1 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories .(Sintex or equivalent make of Capacity - 200-250 Itrs) Nos 1 e E.3.0 EXTERNAL SEWERAGE Itr 0 e Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine Itr			a.5		m			-
b Providing Jaying, testing & commissioning of approved Multi floor trap / Nahani trap with Chilly trap of required sizes, including jointing etc. complete and as directed. (GMGR/Chilly or equivalent) Nos. 5 e SITC RO Water booster pump upto 1 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss,Danfoss,Kirloskar or equivalent) Nos. 1 d SITC RO Water booster pump 0.5 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss,Danfoss,Kirloskar or equivalent) 0 0 f Providing and fixing of PVC water vertical type storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessiories .(Sintex or equivalent make of Capacity - 200-250 ltrs) Nos 1 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories .(Sintex or equivalent make of Capacity - 200-250 ltrs) Nos 1 e E.3.0 EXTERNAL SEWERAGE 0 constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine 0					m		\square	
b Chilly trap of required sizes, including jointing etc. complete and as directed. (GMGR/Chilly or equivalent) Nos. 5 e SITC RO Water booster pump upto 1 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) Nos. 1 d BITC RO Water booster pump 0.5 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) Nos. 1 d SITC RO Water booster pump 0.5 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) 0 0 f Providing and fixing of PVC water vertical type storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessiories. (Sintex or equivalent make of Capacity - 200-250 ltrs) Nos 1 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent make of Capacity - 200-250 ltrs) Nos 1 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent make of Capacity - 200-250 ltrs) Ltr 0 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valv			a.7		m	0	───	
b equivalent Nos. S e SITC RO Water booster pump upto 1 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss,Danfoss,Kirloskar or equivalent) Nos. 1 d SITC RO Water booster pump 0.5 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss,Danfoss,Kirloskar or equivalent) Nos. 1 d SITC RO Water booster pump 0.5 HP Auto Cut Type , mounting with rubber pad & nut bolt (Make Crompton Grundfoss,Danfoss,Kirloskar or equivalent) 0 0 f Providing and fixing of PVC water vertical type storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessiories .(Sintex or equivalent make of Capacity - 200-250 Itrs) Nos 1 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent make) Ltr 0 E.3.0 EXTERNAL SEWERAGE Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine								
Image: Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine Image: Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine			b		Nos.	5		-
e (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) Nos. 1 d STC RO Water booster pump 0.5 HP Auto Cut Type, mounting with rubber pad & nut bolt (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) 0 f Providing and fixing of PVC water vertical type storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessiories .(Sintex or equivalent make of Capacity - 200-250 ltrs) Nos 1 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent make) Nos 1 E.3.0 EXTERNAL SEWERAGE It 0				1 /				
Image: Constructing Strip (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) 0 Image: Constructing Strip (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) 0 Image: Constructing Strip (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) 0 Image: Constructing Strip (Make Crompton Grundfoss, Danfoss, Kirloskar or equivalent) 0 Image: Constructing Strip (Make Crompton Grundfoss, Strip (Star or equivalent)) 0 Image: Constructing Strip (Star or equivalent) 0 Image: Constructing Strip (Star or equivalent make of Capacity - 200-250 ltrs) 0 Image: Constructing Strip (Star or equivalent make of Capacity - 200-250 ltrs) 0 Image: Constructing Strip (Star or equivalent make of Capacity - 200-250 ltrs) 0 Image: Constructing Strip (Star or equivalent make of Capacity - 200-250 ltrs) 0 Image: Constructing Strip (Star or equivalent make of Capacity - 200-250 ltrs) 0 Image: Constructing Strip (Star or equivalent make or eq			e		Nos	1		-
d (Make Crompton Grundloss, Danfoss, Kirloskar or equivalent) 0 f Providing and fixing of PVC water vertical type storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessiories. (Sintex or equivalent make of Capacity - 200-250 ltrs) Nos 1 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessiories. (Sintex or equivalent make of Capacity - 200-250 ltrs) Nos 1 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories. (Sintex or equivalent make of Capacity - 200-250 ltrs) Ltr 0 e E.3.0 EXTERNAL SEWERAGE Image: 0 Image: 0					- 1001	+ .	───	───
f Providing and fixing of PVC water vertical type storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessionies. (Sintex or equivalent make of Capacity - 200-250 ltrs) Nos 1 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve, float valve and necessary accessionies (Sintex or equivalent make of Capacity - 200-250 ltrs) Nos 1 g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessionies (Sintex or equivalent trake of Capacity - 200-250 ltrs) Ltr 0 e E.3.0 EXTERNAL SEWERAGE Image: 0 Image: 0 c Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine Image: 0 Image: 0			d			0		-
accessiories. (Sintex or equivalent make of Capacity - 200-250 ltrs) Image: Construction of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent nake) Image: Construction of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent nake) Image: Construction of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent nake) Image: Construction of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent nake) Image: Construction of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent nake) Image: Construction of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent nake) Image: Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine Image: Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine)		1		Providing and fixing of PVC water vertical type storage tanks of the approved quality, including	1	İ		1
g Providing and fixing of PVC water storage tanks of the approved quality, including making solid work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent nake) Ltr 0 E.3.0 EXTERNAL SEWERAGE Image: Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine Image: Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine)			f		Nos	1		-
g work complete in all respects with gate valve and necessary accessiories(Sintex or equivalent nake) Ltr 0 E.3.0 EXTERNAL SEWERAGE Image Image Image Image Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine Image Image Image		+				<u> </u>	───	───
E.3.0 EXTERNAL SEWERAGE Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine			σ			0		-
Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine			5					
		E.3.0						
sand) RCC top slab with 1:2:4 mix (1 cement :2coarse sand:4graded stone aggregate 20mm				Constructing brick masonry manhole with 1st class bricks in cement mortar 1:5(1 cement:5 fine				
				sand) RCC top slab with 1:2:4 mix (1 cement :2coarse sand:4graded stone aggregate 20mm				
nominal size) foundation concrete 1:4:8 mix (1 cement:4 coarse sand :8 graded stone aggregate								
40mm nominal size) inside and out side plastering 12mm thick with cement mortar 1:3(1 cement								
a ¹³ coarse sand) finished with a floating coat of neat cement inside and rough plaster on outside and making channels in cement concrete 1:2:4 mix(1 cement:2 coarse sand:4 graded stone Each 0			а		Each	0		-
and making channels in cement concrete 1:2:4 mx(1 cement:2 coarse sand:4 graded stone aggregate 20mm nominal size) neatly finished complete as per standard design including								
excavation refilling and disposal of surplus earth.Inside size 80X80 cms and 60 cms deep								
including C.I cover with frame (light duty) 455 x 610 mm internal dimensions total weight of				including C.I cover with frame (light duty) 455 x 610 mm internal dimensions total weight of				
cover and frame not less than 38 kg(wt. Of cover 23 kg and wt.of frame15kg).			1	action and frame not less than 28 kg(wt. Of action 22 kg and wt of frame 15 kg)	1	1	1	1

	1		Gt (18" x18") with 1 st Class brick in cement mortar 1:5 (1 cement : 5 cement) m.s grating with				
	b		pcc & SS Cover, 18" x 18" inside size complete and inside chamber base finish in PCC and	Each	1		-
E.4.0			brick surface to be finished with tile Sanitarywares & Fittings				
E.4.0			Providing & Fixing following fixtures, the rate for the following shall be inclusive of all				
			necessary fixtures, accessories & attachments to make them operational, etc. complete to the				
	а		satisfaction of the Architect				
	ű						
			COST EXCLUDES INTERNAL CONCEALED PLUMBING WITH C.P.V.C. / P.V.C. PIPES				
		WC	ONLY (part of plumbing bog)				
		(Details -	Hindware Enjame or equivalent well mounted closet with Quiet Close cost and cover				
	a.1	Refer	Hindware - Enigma or equivalent- wall mounted closet with Quiet-Close seat and cover (Catalogue no. 92024, Colour - Star white)	No.	0		-
		Toilet	(Catalogue no. 72024, Colour - Star Winte)				
	-	Specs.) Cocealed					
		Cistern	Hindware or equivalent- Conceale Cistern (Concealo) and Face Plate (Concealo - Shell) /		0		
	a.2	with flush	Flushing cistern can be identify from Vendor according to WC.	No.	0		-
		plate					
		Wash Basin					
		(Details -					
	a.3	Refer	Hindware Magma -1719 Artistic Basin-510X360X120 wall hung (white) or equivalent.	No.	0		-
		Toilet					
 		Specs.)					
	a.4	Wash Basin	Hindware table top wash basin Fornte white 91043 or equivalent	No.	1		-
	1	Toilet					
	a.5	accessories	Toilet paper holder with cover - Hindware - (Catalogue no. F880003) or equivalent	No.	0		-
	-						
		Soap					
		Dispenser Wash Basin	Dolphy White ABS Wall Mounted 400 ml Liquid Soap Dispenser/ Dolphy - DSDR 0065 which				
	a.6	(Details -	is manual not automatic. But the alternative specs are mentioned for Automatic will use current	No.	0		-
		Refer	only of Dolphy/censor one will be use for flagship stores only.	110.			
		Toilet					
		Specs.)					
	a.7	Tissue	Dolphy Multifold Stainless Steel Towel Paper Dispenser	No.	1		-
		Dispenser Pillar Cock		110.	-		
	a.8	for Wash	Hindware - Quadra Pillar cock - (Catalogue no. F380001CP, Finish - Chrome) or equivalent	No.	1		-
	4.0	Basin		110.	-		
	a.9	Bib cock	Hindware -Quadra which is actually "Quadra Bib Cock 2 in 1 with wall flange" or equivalent	No.	1		-
	İ	Jet Spray					
		(Health					
	_ 10	Faucet)	Underson Useld, Emert E 160012 CD ADS Well D 1116 Charles Const	N	0		
	a.10	(Details - Refer	Hindware-Health Faucet F 160013 CP ABS With Rubbit Cleaning System	No.	0		-
		Toilet					
		Specs.)					
	a.11	Bottle Trap	Hindware-Addons - Bottle Trap 32mm With 125mm & 175mm Long Wall Connection Pipe	No.	1		-
	-	Sink Mixer	& Wall Flange (ECONOMY MODEL)				
	a.12	For 3 way	Providing and fixing C.P brass wall mounted sink mixer with swinging spout including cutting	Each	1		-
		Sink	and making good the walls where required. (3 way Sink)				
	a.13	40 mm Dia	40 mm CPVC Dia Pipe for 3 way sink for all inclusive fittings	Each	1		-
-		Pipe Kitchen	-				
	a.14	Paper	SS Kitchen Paper Holder 9" (Make : Hindware chrome F840008CP or equivalent)	Each	1		-
		Holder	. ,				
	a.15	Waste	Waste Coupling for 3Way sink and Makeline sink	No.	1		-
 -	<u> </u>	Coupling Waste					
	a.16	Flexible	PVC Waste flexible Pipe of 1.0m length and 25 mm dia (make :SBD/Shineman etc)	No.	0		-
		Pipe					
		Conceal	Conceal coak for makeline sink (Make- Hindware F310003ACP OR equivalent) Regular Body	NG			
	a.17	Coak	Suitable for 15mm Pipe Line with Spindle Extension & Plastic Protection Cap (without Exposed	NO.	1		-
 1	I	1	Parts) OR equivalent				