

| Sai Edge Solutions |                                 |  | Date : 11-3-2024  |     |       |        |  |
|--------------------|---------------------------------|--|---|-----|-------|--------|--|
| Model              |                                 |  | Work Description  | QTY | RATE  | AMOUNT |  |
| 1                  |                                 |  | SUPPLY, of DMB/ODS menu screen as per the below mentioned specification approved.<br>Preferred make: Samsung, Model No. QM32R                           | 4   | 24800 | 99200  |  |
| 2                  |                                 |  | INSTALLATION, MOUNTING TESTING & COMMISSIONING CHARGES  | 4   | 5700  | 22800  |  |
| Panel              | Diagonal Size                   | Class  | 32  |     |       |        |  |
|                    |                                 | Measured   | 31.5  |     |       |        |  |
|                    | Type                            |  | Edge LED BLU  |     |       |        |  |
|                    | Resolution                      |  | FHD (1920 x 1080)   |     |       |        |  |
|                    | Pixel Pitch (mm)                |  | 0.360(H) x 0.360(V)   |     |       |        |  |
|                    | Active Display Area             |  | 698.4(H) x 392.85(V)  |     |       |        |  |
|                    | Brightness(Typ.)                |  | 400   |     |       |        |  |
|                    | Contrast Ratio (Typ.)           |  | 5000:1  |     |       |        |  |
|                    | Viewing Angle(H/V)              |  | 178/178   |     |       |        |  |
|                    | Response Time (G to G)          |  | 8ms(Typ.)   |     |       |        |  |
|                    | Display Colors                  |  | 16.7M(True Display), 1.07B(Ditherd 10bit)   |     |       |        |  |
|                    | Color Gamut                     |  | 72%   |     |       |        |  |
|                    | Operation Hour                  |  | 24/7  |     |       |        |  |
| Haze               |                                 | 2%   |   |     |       |        |  |
| Display            | Dynamic C/R                     |  | MEGA  |     |       |        |  |
|                    | H-Scanning Frequency            |  | 30 ~ 81kHz  |     |       |        |  |
|                    | V-Scanning Frequency            |  | 48 ~ 75Hz   |     |       |        |  |
|                    | Maximum Pixel Frequency         |  | 594MHz  |     |       |        |  |
| Sound              | Speaker Type                    |  | Built in Speaker(10W + 10W)   |     |       |        |  |
|                    |                                 |  | Display Port 1.2 (1)  |     |       |        |  |
| Connectivity       | INPUT                           | RGB  | Display Port 1.2 (1)  |     |       |        |  |
|                    |                                 | VIDEO  | HDMI 2.0 (1)  |     |       |        |  |
|                    |                                 | HDCP   | HDCP2.2   |     |       |        |  |
|                    |                                 | AUDIO  | Stereo mini Jack, HDMI  |     |       |        |  |
|                    | USB                             |  | USB 2.0 x 2   |     |       |        |  |
|                    | OUTPUT                          | RGB  | HDMI 2.0 (Loop-out)   |     |       |        |  |
|                    |                                 | VIDEO  | N/A   |     |       |        |  |
|                    |                                 | AUDIO  | Stereo mini Jack  |     |       |        |  |
|                    |                                 | Power Out  | N/A   |     |       |        |  |
|                    |                                 | USB  | N/A   |     |       |        |  |
|                    | EXTERNAL CONTROL                |  | RS232C(in/out) thru stereo jack, RJ45   |     |       |        |  |
|                    | EXTERNAL SENSOR                 |  | IR  |     |       |        |  |
|                    | Tuner                           |  | N/A   |     |       |        |  |
| Type               |                                 | Internal   |   |     |       |        |  |
| Power Supply       |                                 | AC 100 - 240 V~ (+/- 10 %), 50/60 Hz   |   |     |       |        |  |
| Power              | Power Consumption               | Max(W/h)   | 72  |     |       |        |  |
|                    |                                 | Typical(W/h)   | 44  |     |       |        |  |
|                    |                                 | Rating(W/h)  | 65  |     |       |        |  |
|                    |                                 | BTU(Max)   | 245.5   |     |       |        |  |
|                    |                                 | Sleep mode   | 0.5   |     |       |        |  |
| Off mode           |                                 | N/A  |   |     |       |        |  |
| Mechanical Spec    | Dimension(mm)                   | Set  | 725.1 x 419.8 x 34.6  |     |       |        |  |
|                    |                                 | Package  | 812 x 513 x 120   |     |       |        |  |
|                    |                                 | Set  | 5.7   |     |       |        |  |
|                    | Package                         |  | 8   |     |       |        |  |
|                    | VESA Mount                      |  | 200 X 200   |     |       |        |  |
|                    | Protection Glass                |  | N/A   |     |       |        |  |
|                    | Stand Type                      |  | Foot Stand (Optional)   |     |       |        |  |
| Operation          | Bezel Width (Top/Side/Bot) (mm) |  | 8.8mm(U/L/R/B)  |     |       |        |  |
|                    | Operating Temperature           |  | 0°C- 40°C   |     |       |        |  |
|                    | Humidity                        |  | 10-80%  |     |       |        |  |
| Feature            | Key                             |  | FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0  |     |       |        |  |
|                    | Special                         | HIW  | Temperature Sensor,Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch), Video Wall Daisy Chain(HDCP2.2,4EA,HDCP1.4,7EA), IP5x |     |       |        |  |
|                    |                                 | Rating: Wi-Fi/BT   |   |     |       |        |  |
|                    |                                 | S/W  | Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)   |     |       |        |  |
|                    | Processor                       |  | Cortex A72 1.7GHz Quad-Core CPU   |     |       |        |  |
|                    | On-Chip Cache                   |  | L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB   |     |       |        |  |
|                    | Memory                          |  |   |     |       |        |  |
|                    | Clock Speed                     |  | 1.7GHz  |     |       |        |  |
|                    | Main Memory                     |  | 2.5GB, LPDDR4 1.5GHz 64bit  |     |       |        |  |
|                    | Interface                       |  |   |     |       |        |  |
|                    | Graphics                        |  | Graphic resolution : 1920x1080  |     |       |        |  |
|                    | Storage (FDM)                   |  | Output resolution : 3840x2160 (Scale up from graphic processing result.)  |     |       |        |  |
|                    | Multimedia                      |  | 8GB (3.88GB Occupied by O/S, 4.12GB Available)  |     |       |        |  |
| IO Ports           |                                 | *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9, *Audio Decoder : AC3 (DD), MPEG |   |     |       |        |  |
| Operating System   |                                 | USB 2.0  |   |     |       |        |  |
|                    |                                 |  | Tizen 4.0 (VDLinux)   |     |       |        |  |
| Certification      | Safety                          |  | 60950-1   |     |       |        |  |
|                    | EMC                             |  | Class B   |     |       |        |  |
|                    | Environment                     |  | N/A   |     |       |        |  |
| Security           |                                 |  | 802.1x(WPA2 Enterprise) - EAP-TLS, EAP-TTLS, EAP-PEAP   |     |       |        |  |
| Accessories        | Included                        |  | Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries  |     |       |        |  |
|                    | Optional                        | Stand  | STN-L3240E  |     |       |        |  |
|                    |                                 | Mount  | WMN4070SE   |     |       |        |  |
|                    |                                 | Specialty  | CML400XK  |     |       |        |  |
|                    |                                 | Media Player   |   | N/A |       |        |  |

**NOTE :**

GST Extra

All 4 tv installation will be scheduled in 1 day need downtime according

Its Adani responsibility to arrange the gate pass once team committed Dates ,in case of any reason if we will not get access in that case 1500 charge extra per tv for the same