



UNDER COUNTER CHILLERS 2 DOORS AND 3 DOORS



- Tropicalised for high ambient temperatures
- Eco-friendly refrigerant
- Food grade stainless steel unit
- Odourless operation due to continuous air circulation
- Uniform cooling by forced air circulation
- Self-closing doors

Technical Specifications

| DESCRIPTION | UC2100A | UC3100A | UC2100E | UC3100E | UC2100GP | UC3100GP | UC2100GC | UC3100GC |
|-----------------------------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Capacity (Ltrs) | 260 | 410 | 260 | 400 | 260 | 400 | 260 | 400 |
| Temperature Range | 0° ~ +12°C | 0° ~ +12°C | 0° ~ +12°C | 0° ~ +12°C | 0° ~ +12°C | 0° ~ +12°C | 0° ~ +12°C | 0° ~ +12°C |
| No. of Doors (Nos.) | 2 | 3 | 2 | 3 | 2 | 3 | 2 | 3 |
| Type Of Doors (Int/Ext) | SS-304/201 | SS-304/201 | SS-201/201 | SS-201/201 | SS-304/201 | SS-304/201 | SS-201/201 | SS-201/201 |
| Shelves Qty (Nos.) | 2 | 3 | 2 | 3 | 2 | 3 | 2 | 3 |
| Gn Pan | GN2/1 | GN2/1 | GN2/1 | GN2/1 | GN2/1 | GN2/1 | GN2/1 | GN2/1 |
| Refrigerant Gas (Type/Charge) | R134a/245g | R134a/245g | R134a/260g | R134a/260g | R290/50g | R290/50g | R290/50g | R290/50g |
| Voltage Supply & Frequency (V-Hz) | 220-240V/50Hz | 220-240V/50Hz | 220-240V/50Hz | 220-240V/50Hz | 220-240V/50Hz | 220-240V/50Hz | 220-240V/50Hz | 220-240V/50Hz |
| Max Input Power | 340W | 340W | 350W | 350W | 255W | 255W | 255W | 255W |
| Current Amps | 1.97A | 1.97A | 2.2A | 2.2A | 1.8A | 2.0A | 1.8A | 2.0A |
| Defrost | Automatic | Automatic | Automatic | Automatic | Automatic | Automatic | Automatic | Automatic |
| Thermostat | Digital | Digital | Digital | Digital | Digital | Digital | Digital | Digital |
| External Dimension (WxDXH) mm | 1380x700x850 | 1815x700x850 | 1350x700x850 | 1800x700x850 | 1365x700x850 | 1805x700x850 | 1365x700x850 | 1805x700x850 |
| Net Weight (Kg) | 112 | 135 | 100 | 124 | 96 | 116 | 96 | 116 |
| Gross Weight (Kg) | 136 | 159 | 118 | 149 | 115 | 142 | 115 | 142 |

As a continuing policy of research and development in Blue Star, the design, features, technical specifications are subject to change without prior notice. The product images shown are for reference only and actual products may differ. Values mentioned are under standard tested conditions in lab. Actual performance values may vary with different ambient conditions. Features may vary from model to model.



Scan QR Code - Blue Star Customer Care Mobile App



SMS "SERVICE" to 57575



Download Blue Star Customer Care Mobile App from App Store & Google Play



To know more about Blue Star, visit www.bluestarindia.com, email us at coolingsolutions@bluestarindia.com or SMS 'COOL' to 57575

