

**SIC 1160**

## Specifications

DESCRIPTION	2 way in-ceiling speaker
TRANSDUCER COMPLEMENTS	1 x 6" coaxial speaker
SPL @ RATED POWER	98 dB @ 10 W
NOMINAL IMPEDANCE	8 Ohm
SENSITIVITY (1 W 1M)	88 dB (half space)
FREQUENCY RESPONSE	70 Hz ~ 20 kHz (-3 dB)
FREQUENCY RANGE	60 Hz ~ 22 kHz (-10 dB)
POWER HANDLING DIRECT MODE	20 W
POWER TAPS @ 70V	1.25, 2.5, 5 W
POWER TAPS @ 100V	2.5, 5, 10 W
COLOURS	White
OUTER DIMENSIONS (DEPTH X DIA)	82 x 228 mm
WALL/CEILING CUT-OUT	196 mm
NET WEIGHT	1.9 kg
MOUNTING OPTIONS	Ceiling mount

**SIC 1260****Specifications**

DESCRIPTION	2 way in-ceiling speaker
TRANSDUCER COMPLEMENTS	1 x 6" coaxial speaker
SPL @ RATED POWER	100 dB @ 20 W
NOMINAL IMPEDANCE	8 Ohm
SENSITIVITY (1 W 1M)	88 dB (half space)
FREQUENCY RESPONSE	85 Hz ~ 18 kHz (-3 dB)
FREQUENCY RANGE	70 Hz ~ 20 kHz (-10 dB)
POWER HANDLING DIRECT MODE	60 W
POWER TAPS @ 70V	1.25, 2.5, 5, 10 W
POWER TAPS @ 100V	2.5, 5, 10, 20 W
COLOURS	White
OUTER DIMENSIONS (DEPTH X DIA)	110 x 237 mm
WALL/CEILING CUT-OUT	203 mm
NET WEIGHT	2.2 kg
MOUNTING OPTIONS	Ceiling mount

**SONODYNE®**

**HS 250**

## Specifications

OUTPUT POWER PER CHANNEL	250 W
OUTPUT MODE	4 Ohm-70V-100V
INPUT CHANNELS	6 MIC or Line - Bluetooth - MP3 and Aux
INPUT VOLTAGE	100-240Vac 50-60Hz
MOUNTING	1RU
FREQUENCY RESPONSE	100Hz - 16kHz
THD+N	< 0.3%
SIGNAL TO NOISE RATIO	> 75dB
INPUT SENSITIVITY	0dBu
COOLING	Fan-assisted
SHIPPING DIMENSION (W x D x H)	520mm x 520mm x 106mm
SHIPPING WEIGHT	9.0 Kg
PRODUCT DIMENSION (W x D x H)	438mm x 406mm x 44mm
NET WEIGHT	6.8 Kg

**SOW 6150**

## Specifications

SYSTEM	Passive 2 way bass reflex
TRANSDUCER COMPLEMENTS: HF	1 x 1" dome tweeter
TRANSDUCER COMPLEMENTS: LF	1 x 5" woofer
FREQUENCY RESPONSE	80Hz ~ 20kHz, ± 6dB
POWER HANDLING DIRECT MODE	60W
POWER TAPS 100V	3.75W, 7.5W, 15W, 30W
POWER TAPS 70V	1.77W, 3.75W, 7.5W, 15W
NOMINAL IMPEDANCE	8 Ohm
SENSITIVITY (1 W 1M)	88dB (half space)
MAX SPL DIRECT MODE	105dB
INPUT	Push type terminal, colour coded
IP RATING	IP65
GRILL	Aluminium mesh powder coated
ENCLOSURE	Polypropylene
COLOURS	White/ Black
DIMENSIONS WITHOUT BRACKET (HXWXD) MM	252 x 176 x 148
NET WEIGHT	2.3kg
MOUNTING ACCESSORY	Pan and tilt wall-mounting bracket