

**ES 250****Specifications**

|                               |                          |
|-------------------------------|--------------------------|
| OUTPUT POWER PER CHANNEL      | 250 watt                 |
| FREQUENCY RESPONSE            | 40Hz - 20kHz             |
| OUTPUT MODE                   | 4 Ohm-100V               |
| THD+N                         | < 0.2%                   |
| INPUT CHANNELS                | 4 MIC or Line            |
| SIGNAL TO NOISE RATIO         | > 80dB                   |
| INPUT VOLTAGE                 | 230Vac 50Hz              |
| INPUT SENSITIVITY             | MIC: 1.2mV - Line: 160mV |
| MOUNTING                      | 2RU                      |
| COOLING                       | Fan-assisted             |
| DIMENSIONS (WXDXH) MM         | 483 x 365 x 88           |
| SHIPPING DIMENSIONS (WXDXH)MM | 545 x 460 x 160          |
| NET WEIGHT                    | 11.8kg                   |

**SONODYNE®**

Products of the **MUKHERJEE INNOVATION CENTRE**

SONODYNE, 98 NB Block E New Alipore, Kolkata 700053, INDIA 1-800-123-37-36 • [response@sonodyne.com](mailto:response@sonodyne.com) • [www.sonodyne.com](http://www.sonodyne.com)

SONODYNE, 98 NB Block E New Alipore, Kolkata 700053, INDIA 1-800-123-37-36 • [response@sonodyne.com](mailto:response@sonodyne.com) • [www.sonodyne.com](http://www.sonodyne.com)