

SIC 1160**Specifications**

DESCRIPTION	2 way in-ceiling speaker
TRANSDUCER COMPLEMENTS	1 x 6" coaxial speaker
SPL @ RATED POWER	98 dB @ 10 W
NOMINAL IMPEDANCE	8 Ohm
SENSITIVITY (1 W 1M)	88 dB (half space)
FREQUENCY RESPONSE	70 Hz ~ 20 kHz (-3 dB)
FREQUENCY RANGE	60 Hz ~ 22 kHz (-10 dB)
POWER HANDLING DIRECT MODE	20 W
POWER TAPS @ 70V	1.25, 2.5, 5 W
POWER TAPS @ 100V	2.5, 5, 10 W
COLOURS	White
OUTER DIMENSIONS (DEPTH X DIA)	82 x 228 mm
WALL/CEILING CUT-OUT	196 mm
NET WEIGHT	1.9 kg
MOUNTING OPTIONS	Ceiling mount

SONODYNE®

Products of the **MUKHERJEE INNOVATION CENTRE**

SONODYNE, 98 NB Block E New Alipore, Kolkata 700053, INDIA 1-800-123-37-36 • response@sonodyne.com • www.sonodyne.com

SONODYNE, 98 NB Block E New Alipore, Kolkata 700053, INDIA 1-800-123-37-36 • response@sonodyne.com • www.sonodyne.com