



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
--	---------------------------	--	----------------------	--	-------------------

TECHNICAL DATA	STD	THREE-PHASE	UK
EXTERNAL DIMENSIONS			
width	450 mm		
depth	535 mm		
height	700 mm		
WEIGHT	37 kg		
VOLTAGE	230V 50Hz	400V 3N 50Hz	240V 50Hz
POWER REQUIRED	3200 W	4400 W	3010 W
WATER HARDNESS	2-8 °F		
INLET WATER PRESSURE	200-400 kPa		
CROCKERY DIMENSIONS			
plates diameter (LS version)	295mm		
dishes max. height	305mm		
RACK DIMENSIONS	400X400mm		
RACK EQUIPMENT	2XC121 - 1X10728 - 1X15060		
WASHING CYCLES (sec)	1(120)		
WATER SUPPLY 55°C			
racks/h(*) ⁽¹⁾	30		
WATER SUPPLY 10°C			
racks/h(*) ⁽¹⁾	16	22	14
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	1.8 L		
BOILER CAPACITY	3.4 L		
BOILER HEATING ELEMENT	2800 W	4000 W	2610 W
RINSING TEMPERATURE (SET)	85°C		
TANK CAPACITY	14.5 L		
TANK HEATING ELEMENT	1250 W		
TANK TEMPERATURE (SET)	55°C		
PUMP POWER	400 W (185 L/min ^{***})		
DRAIN PUMP (optional)	25 W h MAX draining 0.8m (40 L/min ^{***})		
NOISE (dB(A)±0.7)	60.6(CF)	61.2(LS)	

(*) STANDARD THERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.